

C1200-C

ISOLATION FLOOR CLEANOUT MODEL VARIATIONS

C1200-C-S FLOOR CLEANOUT WITH SQUARE TOPMARKER

MODEL NUMBER	WT.Lbs	COVER SIZE	OUTLET SIZE	LACQUERED CAST IRON BODY WITH NICKEL BRONZE (-1)
	Lbs			
C1202-C-S	17.5	5" x 5"	2"	\$1,341.00
C1203-C-S	16.75	5" x 5"	3"	\$1,341.00
C1204-C-S	17.50	5" x 5"	4"	\$1,341.00
C1205,6-C-S	17.75	5" x 5"	5", 6"	\$1,582.00

C1200-C OPTIONAL VARIATIONS:

SUFFIX	DESCRIPTION	LIST PRICE
-4	Ductile iron top assembly	See above
-6	Security screws (TR25 Torx and pin) (H-1039A)	\$72.00
-11	All acid resistant epoxy coated	\$797.00
-13	All galvanized	\$797.00
-28	All 304 Stainless steel bodies (2",3",4" No Hub Only)	\$1,904.00
SUFFIX	DESCRIPTION	LIST PRICE
-30	PVC socket connection body* (2",3",4")	No Add
-31	ABS socket connection body* (2",3",4")	No Add
-34	T-cone plug and gasket (C1440 Series)	\$289.00
NH	No hub outlet (2", 3", 4")	Standard
P	Push on outlet (2", 3", 4")*	No Add
T	Threaded outlet (2", 3", 4")	\$64.00
X	Inside caulk outlet (2", 3", 4")	No Add