

R1200-W

LARGE SUMP ROOF DRAIN WITH ADJUSTABLE INTERNAL STANDPIPE DAM

LACQUERED CAST IRON BODY WITH:

| MODEL NUMBER | WT.Lbs | OUTLET SIZE | POLY DOME (STANDARD) | CAST IRON DOME (-M) |
|--------------|--------|-------------|----------------------|---------------------|
| R1202,3,4-W | 22 | 2" , 3" ,4" | \$886.00 | \$1,051.00 |
| R1205, 6-W | 23.5 | 5" , 6" | \$1,128.00 | \$1,293.00 |

R1200-W OPTIONAL VARIATIONS

| SUFFIX | DESCRIPTION | LIST PRICE |
|--------|---------------------------------------------------------------------|------------|
| -6 | Vandal proof (Metal dome only)(H-1029) | \$98.00 |
| -11 | Acid resistant epoxy coated body, membrane clamp & dome | \$1,070.00 |
| -12 | Galvanized metal dome | \$287.00 |
| -12A | Galvanized body and membrane clamp | \$756.00 |
| -12B | Galvanized metal dome and membrane clamp | \$520.00 |
| -13 | Galvanized body, membrane clamp and dome | \$1,073.00 |
| -28 | Stainless steel body (Type 304) | \$2,830.00 |
| -30 | PVC socket connection body*(2" ,3" , 4") | No Add |
| -31 | ABS socket connection body*(2" ,3" , 4") | No Add |
| -81 | Rough bronze dome (A2-MDL-81) (to poly dome) | \$652.00 |
| -83 | Stainless steel mesh screen over dome (A2-SSD) (to poly dome) | \$396.00 |
| -90 | Threaded side outlet (cast iron only) (2" ,3" ,4") (N/A in -30,-31) | \$290.00 |
| -90-NH | No hub side outlet (cast iron only) (2" ,3" ,4")(N/A in -30,-31) | \$290.00 |
| -B | Sump receiver (A2-BP) (A2-BP-90 for R1200-90 Series) | \$213.00 |
| -C | Secondary clamp (A2-C3) | \$191.00 |

| | | |
|-------------|--------------------------------------------------------------------------------|------------|
| -E | Adjustable extension (See page 114, point #7) | \$571.00 |
| -EG | Galvanized adjustable extension | \$846.00 |
| -F1,-F2,-F3 | Accuflow (parabolic weir) (A2-F1, A2-F2, A2-F3)(R1200-Z only) | \$968.00 |
| -G | Ballast guard (A2-BG) | \$618.00 |
| -HC | Adj. ballast guard with secondary clamp | \$809.00 |
| -JC | Ballast guard with secondary clamp | \$809.00 |
| M-80 | Low aluminum dome (4 1/4" high) (A2-MDL-80) (to poly dome) | \$195.00 |
| P | Push on outlet, (2", 3", 4" or 6") Specify POG-6 for C.I. pipe | No Add |
| -R | 2" external water dam (A2-WD) (R1200-Z only) | \$183.00 |
| T | Threaded outlet, (2", 3", 4", 5" or 6") | \$62.00 |
| -U | Underdeck clamp (A2-C3) (A368-DC for 8") | \$191.00 |
| -U3 | Underdeck clamp with cut away side (A2-C3-C0) | \$385.00 |
| -V | Fixed extension, (2",3",4") (A2-V2, A2-V3 or A2-V4) | \$521.00 |
| -VG | Galvanized fixed extension, (2", 3", or 4") | \$785.00 |
| -W | Adjustable water dam (5" high x 4" Diameter) (A2-C3-W and W-31) (R1200-Z only) | \$696.00 |
| -W-1 | Water proofing flange (A2-W-1) | \$348.00 |
| -W2 | 2" internal water dam (A2-C3- W and W -31)(R1200-Z only) | \$331.00 |
| -W3 | 3" internal water dam (A2-C3- W and W -31)(R1200-Z only) | \$331.00 |
| -W4 | 4" internal water dam (A2-C3- W and W -31)(R1200-Z only) | \$331.00 |
| X | Inside caulk outlet, (2", 3", 4", 5" or 6") | No Add |
| -Z | Extended wide flange on body (20"Dia. x 1/4 thick) | \$1,039.00 |