

R1220-JC

MEDIUM SUMP DRAIN WITH STAINLESS STEEL BALLAST GUARD

LACQUERED CAST IRON BODY WITH:

| MODEL NUMBER | WT.Lbs | OUTLET SIZE (NO HUB STANDARD) | CAST IRON DOME (-M) |
|----------------|--------|-------------------------------|---------------------|
| R1222,3,4,6-JC | 21.00 | 2",3",4",6" | \$1,106.00 |

R1220-JC OPTIONAL VARIATIONS

| SUFFIX | DESCRIPTION | LIST PRICE |
|--------|---|------------|
| -6 | Vandal proof (Metal dome only)(H-1029) | \$90.00 |
| -11 | Acid resistant epoxy coated body, membrane clamp & dome | \$802.00 |
| -12 | Galvanized metal dome | \$100.00 |
| -12A | Galvanized body and membrane clamp | \$260.00 |
| -13 | Galvanized body, membrane clamp and dome | \$310.00 |
| -83 | Stainless steel mesh screen over dome | \$366.00 |
| -B | Sump receiver (A5-BP) | \$202.00 |
| -C | Secondary clamp (A5-C3) | \$118.00 |
| -E | Adjustable extension (See page 114, point #7) | \$397.00 |
| -EG | Galvanized adjustable extension | \$890.00 |
| -G | Ballast guard (A5-BG) | \$494.00 |
| -HC | Adj. ballast guard with secondary clamp | \$612.00 |
| -JC | Ballast guard with secondary clamp | \$612.00 |
| -R | 2" external water dam (A5-WD) | \$152.00 |
| -U | Underdeck clamp (A5-C3) | \$118.00 |
| -U3 | Underdeck clamp with cut away side (A5-C3-U) | \$118.00 |
| -W-1 | Water proofing flange (A5-W-1) | \$348.00 |
| X | Inside caulk outlet, (2", 3", 4", 5" or 6") | No Add |
| -Z | Extended wide flange on body (20" Dia. x 1/4 thick) | \$1,037.00 |
| -5 | Cast iron sediment bucket (A2-MB) for R1220-PR only | \$202.00 |