

R1220-RS MEDIUM SUMP ROOF DECK CONDENSATE RECEPTOR DRAIN

LACQUERED CAST IRON BODY WITH:

MODEL NUMBER	WT.Lbs	OUTLET SIZE (NO HUB STANDARD)	POLY DOME (STANDARD)
R1222,3,4,6-RS	28.00	2",3",4",6"	\$652.00

R1220-RS OPTIONAL VARIATIONS

SUFFIX	DESCRIPTION	LIST PRICE
-6	Vandal proof (Metal dome only)(H-1029)	\$104.00
-11	Acid resistant epoxy coated body, membrane clamp & dome	\$922.00
-12	Galvanized metal dome	\$115.00
-12A	Galvanized body and membrane clamp	\$299.00
-13	Galvanized body, membrane clamp and dome	\$357.00
-83	Stainless steel mesh screen over dome	\$421.00
-B	Sump receiver (A5-BP)	\$232.00
-C	Secondary clamp (A5-C3)	\$136.00
-E	Adjustable extension (See page 114, point #7)	\$457.00
-EG	Galvanized adjustable extension	\$1,024.00
-G	Ballast guard (A5-BG)	\$568.00
-HC	Adj. ballast guard with secondary clamp	\$704.00
-JC	Ballast guard with secondary clamp	\$704.00

-R	2" external water dam (A5-WD)	\$175.00
-U	Underdeck clamp (A5-C3)	\$136.00
-U3	Underdeck clamp with cut away side (A5-C3-U)	\$136.00
-W-1	Water proofing flange (A5-W-1)	\$400.00
X	Inside caulk outlet, (2", 3", 4", 5" or 6")	No Add
-Z	Extended wide flange on body (20" Dia. x 1/4 thick)	\$1,193.00
-5	Cast iron sediment bucket (A2-MB) for R1220-PR only	\$232.00
