

R1220

MEDIUM SUMP ROOF DRAIN

LACQUERED CAST IRON BODY WITH

MODEL NUMBER	WT.Lbs	OUTLE SIZE (NO HUB STANDARD)	CAST IRON DOME (-M)
R1222, 3, 4, 6	26.50	2", 3", 4", 6"	\$857.00

R1220, R1220-EU, R1220-G, R1220-JC, R1220-PR, R1220-R AND R1220-RS OPTIONAL VARIATIONS

SUFFIX	DESCRIPTION	LIST PRICE
-6	Vandal proof (Metal dome only) (H-1029)	\$162.00
-11	Acid resistant epoxy coated body, membrane clamp & dome	\$1,389.00
-12	Galvanized metal dome (add to -M Price)	\$176.00
-12A	Galvanized body and membrane clamp	\$455.00
-13	Galvanized body, membrane clamp and dome	\$540.00
-83	Stainless steel mesh screen over dome	\$639.00
-B	Sump receiver (A2-BP-90)	\$355.00
-E	Adjustable extension (See page 110, point #7)	\$691.00
-EG	Galvanized adjustable extension	\$1,551.00
-G	Ballast guard (A5-BG)	\$857.00
-HC	Adjustable ballast guard with secondary clamp	\$1,064.00
-JC	Ballast guard with secondary clamp	\$1,064.00
-R	2" external water dam (A5-WD)	\$269.00
-U	Underdeck clamp (A5-C3)	\$207.00
-U3	Underdeck clamp with cut away side (A5-C3-U)	\$207.00
-W-1	Water proofing flange (A5-W-1)	\$607.00
X	Inside caulk outlet (2", 3", 4", 6")	No Add
-Z	Extended wide flange on body (20" dia. x 1/4" thick)	\$1,961.00
-5	Cast iron sediment bucket (A2-MB) for R1220-PR only	\$354.00