

T1500-3 T1500-3 - 6" Wide, Neutral Sloped Fibre Reinforced Concrete Trench Drain System with integral Stainless Steel rail & grates

Fabricated Grates (Available in either 1/2 meter (-500) or full meter sections)				
Part #	Order Guide Suffix	Description	List Price, Each, Add	List Price, Per Foot, Add
T1500-PG-PGC	-PGC	ADA Heelproof, COMBee composite, perforated grate - Class C, 1/2 Meter long	see FILCOTEN book	see FILCOTEN book
T1500-PG-FSSC	-FSSC	Stainless Steel, Fabricated Reinforced Slotted grate - Class C, 1 meter long	see FILCOTEN book	see FILCOTEN book
T1500-PG-FSSC-500	-FSSC-500	Stainless Steel, Fabricated Reinforced Slotted grate - Class C, 1/2 meter long	see FILCOTEN book	see FILCOTEN book
T1500-PG-FSPC	-FSPC	Stainless Steel, Fabricated Reinforced Perforated grate - Class C, 1 meter long	see FILCOTEN book	see FILCOTEN book
T1500-PG-FSPC-500	-FSPC-500	Stainless Steel, Fabricated Reinforced Perforated grate - Class C, 1/2 meter long	see FILCOTEN book	see FILCOTEN book

Note: All grates are made with a four point (snap in) grate locking system.

End caps / outlets / accessories				
Part #	Order Guide Suffix	Description	List Price, Each, Add	
T1500-PBDS-SS	-PBDS	Stainless Steel bottom dome strainer	see FILCOTEN book	
T1500-PBO2	-PBO2	2" no hub bottom outlet (PVC material)	see FILCOTEN book	
T1500-PBO3	-PBO3	3" no hub bottom outlet (PVC material)	see FILCOTEN book	
T1500-PBO4	-PBO4	4" no hub bottom outlet (PVC material)	see FILCOTEN book	
T1500-PEC	-PEC	End cap (PVC material)	see FILCOTEN book	
T1500-PEO2	-PEO2	2" no hub end outlet (PVC material)	see FILCOTEN book	
T1500-PEO3	-PEO3	3" no hub end outlet (PVC material)	see FILCOTEN book	
T1500-PEO4	-PEO4	4" no hub end outlet (PVC material)	see FILCOTEN book	
T1500-PGLVP	-6	Vandal proof grate lockdown (stainless steel)	see FILCOTEN book	
T1500-REB	-REB	Rebar support (for each joint connection)	see FILCOTEN book	
T1500-ST	-ST	Step connector to connect T1500N-3, T1510N-3 and T1520N-3 bodies	see FILCOTEN book	

Fabrications				
Part #	Order Guide Suffix	Description	List Price, Each, Add	
T1500-3-CUT	-CUT	Cutting / per cut - Net Price only	see FILCOTEN book	
Tees	-TEE	Fabricated tee (available in T1500N-TEE, T1505N-TEE,	see FILCOTEN book	
45°	-45	45 degree body section	see FILCOTEN book	
90°	-90	90 degree body section	see FILCOTEN book	

Note: The FILCOTEN fibre re-enforced concrete trench drain systems are also available with integral stainless steel rails in 8" widths (T1700 Series), and a shallow (2.36" deep) 6" width (T1560 Series). See the FILCOTEN booklet or the www.mifab.com website for more information.

PER FOOT PRICE CALCULATION: See the FILCOTEN booklet for pricing.

Note: The T1500-3 Series (with integral stainless steel rails) are available in neutral sloped trench drain bodies only. The T1500-ST (step connector) needs to be used to connect the T1500N-3 body to the T1510N-3 and also to connect the T1510N-3 body to the T1520N-3.