



REFERENCE GUIDE



DISTRIBUTED BY: **MIFAB**

BEECO CATALOG

Atmospheric Vacuum Breaker Lead Free Backflow



BEECO: ASVB
WILKINS: 35
WATTS: 288
FEBCO (no LF): 710
APOLLO: 38LF-100

Pressure Vacuum Breaker Lead Free Backflow



BEECO: PVB
WILKINS (no LF): 720A or 710
WATTS: LF800
FEBCO (no LF): 765
APOLLO: 4ALF-500

Small Diameter DC's Lead Free Backflow



BEECO: FDC
WILKINS: 950XL3 / 350XL / 950XLT
WATTS: LF007 / LF709 / LF719
FEBCO: LF850
APOLLO: 4ALF-100

Small Diameter RP's Lead Free Backflow



BEECO: FRP
WILKINS: 975XL3 / 375XL / 975XL2
WATTS: LF009 / LF909
FEBCO: LF825Y / LF860
APOLLO: 4ALF-200

Dual Check Lead Free Backflow



BEECO: DUAL CHECK
WILKINS: 700XL
WATTS: LF7R
CASH ACME: BF
APOLLO: 4ALF-300

Vented Dual Check Backflow



BEECO: DCAV
WILKINS: 760
WATTS: 9D
CASH ACME: BFP
APOLLO: 4ALF-400

Large Stainless Steel Backflow Barracuda RP - OSY & NRS



BEECO: FRP SS
WILKINS: 375A
WATTS: 957
APOLLO: 4ALF-200

Large Epoxy Coated Ductile Iron Backflow RP - OSY & NRS



BEECO: FRP
WILKINS: 375A
WATTS: LF909
FEBCO: LF860

Large Stainless Steel Backflow Barracuda DC - OSY & NRS



BEECO: FDC SS
WILKINS: 350
WATTS: 774
APOLLO: 4ALF-100

Large Epoxy Coated Ductile Iron Backflow DC - OSY & NRS



BEECO: FDC
WILKINS: 350A
WATTS: LF709
FEBCO: LF850

Large Epoxy Coated Ductile Iron Backflow RPDA - OSY



BEECO: FRP - RPDA
WILKINS: 375ADA
WATTS: LF994 RPDA
FEBCO: LF866
APOLLO: 4ALF-700

Large Epoxy Coated Ductile Iron Backflow DCDA - OSY



BEECO: FDC - DCDA
WILKINS: 350 ADA
WATTS: LF774 DCDA
FEBCO: LF856
APOLLO: 4ALF-600

Pressure Reducing Valve Direct Acting



BEECO: PRV-F
WILKINS: 600XL3
WATTS: LF25AUB (EXACT FIT & THREAD SPEC)
CASH ACME: E3
APOLLO: 36ELF

Compact Double Union Pressure Reducing Valve



BEECO: PRV-C
WILKINS: NR3XL / 70XL
WATTS: N45 / N55
CASH ACME: EB45
APOLLO: 36ELF

ACV Pilot Operated Pressure Reducing Valve



BEECO: ACV
WILKINS: ZW209
WATTS: LF115F OR M
CLA-VAL: 90-01
SINGER: 106-PR
BERMAD: 720



Water Heater Shut Off Thermal Expansion Valve Standard Fully Adjustable & With All Drain Fittings



BEECO: MI-CONTROL
WILKINS: BVECXL
WATTS: LFBRVM1
SIOUX CHIEF: TERV
APOLLO: 78LF714RV

NOT
ADJUSTABLE