

SPECIAL PRECAUTIONS

1. HIGH TEMPERATURE KITCHEN WATER
If there is water entering the interceptor at over 150°F, a drain water tempering valve and approved backflow prevention assembly must be installed. Generally, state and local plumbing codes prohibit water above 150°F from being discharged into the sewer.

2. HYDROSTATIC SLABS (OR PRESSURE SLABS)
Interceptor must be enclosed in a water concrete vault when installed under a hydrostatic slab (slab designed to withstand upward lift, typically caused by hydrostatic pressure).

3. MAXIMUM WATER LEVEL
The water level will never go beyond the level height of Inlet/Outlet connection.

4. HIGH WATER TABLE INSTALLATIONS
Interceptor and riser cannot withstand excessive water table height - see max water table height in figure 3. If possible, interceptor and riser should be installed in a water tight concrete vault or backfill with concrete or flowable fill (pour wet concrete and flowable backfill in stages to avoid crushing the interceptor). BIG MAX models buried in high water table are required to be installed with an anchor kit. High Risk Areas: Floodplains, tidal surge and high storm-water areas.

CONCRETE SLAB SUBJECT TO HYDROSTATIC PRESSURE

WATERTIGHT CONCRETE VAULT

MAX WATER TABLE HEIGHT FOR DIRECT BURIAL

FIG. 1

FIG. 2

FIG. 3

FIG. 4

SPECIAL PRECAUTIONS

5. ABOVE GRADE INSTALLATION SUPPORT - ANCHOR KITS
Anchor kit is recommended for installation in high water table conditions to prevent float out. Necessity to be determined by Project Engineer. Place Anchor hook over handle on interceptor. Bolt hardware through hole of anchor hook, to ensure hook does not become removed. Anchor plate may be bolted to concrete slab using provided holes.

FIG. 5

FIG. 6

INSTALLATIONS

BELOW GRADE/BACKFILL INSTALL:

1. Install the interceptor(s) as close as practical to the fixtures being served.
2. The excavation must be a minimum of 12" greater on all sides of the tank.
3. The depth of the excavation must be greater than 6" on the bottom of the interceptor.
4. Backfill while filling the interceptor with water at an equal rate until you reach the inlet/outlet. (Do not pack the backfill)
5. Fully install the double wall corrugated pipe and lid prior to backfilling.
6. Concrete or finishing material requirements is to be determined by the specifying engineer.
7. Encase the interceptor in well-packed 3/4" rock, or sand. Do not compact backfill around interceptor.
8. To prevent float out; the Anchor kit is recommended for installations in high water table conditions. This is to be determined by the specifying engineer.

FINISHED CONCRETE SLAB
Slab must extend 18" minimum outside the footprint of the unit. **Pedestrian traffic areas:** 4" Thick reinforced concrete slab required. **Vehicular traffic areas:** Minimum 8" thick concrete slab with rebar is required.

Thickness of concrete around cover to be determined by specifying engineer. If traffic loading is required, the concrete slab dimensions shown are for guiding purposes only. Concrete to be 28 day compressive strength to 4,000 PSI. Use #4 rebar (1/2") grade 60 steel per ASTM A631s connected with fire wire. Rebar to be 2-1/2" from edge of concrete and spaced in a 12" grid with 4" spacing around access openings.

FIG. 11

FIG. 12

FIG. 13

INSTALLATIONS

EXTENSION COLLAR INSTALLATION

1. Set the BIG MAX unit height to grade by installing the 3/8" diameter corrugated pipe onto the top opening(s) of the body, then insert the lid on top to measure and adjust the finished height from the top to grade. If less extension is needed, measure the required dimension and mark the extension. Then, cut to fit with a saw. The extension system is ADS pipe and is designed to be field cut as needed. If a longer extension is required to meet grade, new ADS pipe can be purchased and cut to length in order to equal grade. (ADS pipe part #18N12)
2. Install the Pipe Gasket between the bottom ribs. Then firmly press the 3/8" diameter pipe into the top opening(s) of the interceptor. It will bottom out at the pipe stop. The gasket is designed to fit tightly around the extension collar. Pry the gasket into place with a pry tool can save time and make this process easier. Watch the installation video at www.bti.us/ADS-gasket
3. Insert the extension collar and pipe gasket onto the opening of the BIG MAX. Press firmly until the extension is seated inside the provided recessed channel. The BIG MAX is designed to fit tightly, and installation can be made easier by wetting the receiving area with mild soapy water. This will reduce the friction and allow the extension to press more easily into place.
4. Remove the cover from the lid assembly to see the predrilled screw holes. Affix the lid gasket with the self adhesive onto the underside of the collar. Place lid assembly onto the top of the corrugated pipe. Connect the lid assembly collar to the pipe with the 6 self tapping screws into the countersunk holes. Replace lid back onto the lid assembly collar.
5. When installing the collar on concrete roads, an 8 inch-wide concrete ring beam with a 3/4" wide guard circle around it should be poured between the collar and brick setting to make the surrounding compaction level and unmovable.
6. When installing the collar on a bituminous road, the collar must be installed after the road is paved. Roller compaction by construction equipment around the collar must be avoided. A hole that is slightly larger than the collar should be inserted before pouring the pavement. The reserved hole can help ensure the installation quality and prolong the usefulness of the installation.

FIG. 14

FIG. 15

PUMPER HOSE REPRESENTATION

FIG. 16

FIG. 17

FIG. 18

FIG. 19

FIG. 20

FIG. 21

FIG. 22

FIG. 23

FIG. 24

FIG. 25

FIG. 26

FIG. 27

FIG. 28

FIG. 29

FIG. 30

FIG. 31

FIG. 32

FIG. 33

FIG. 34

FIG. 35

FIG. 36

FIG. 37

FIG. 38

FIG. 39

FIG. 40

FIG. 41

FIG. 42

FIG. 43

FIG. 44

FIG. 45

FIG. 46

FIG. 47

FIG. 48

FIG. 49

FIG. 50

FIG. 51

FIG. 52

FIG. 53

FIG. 54

FIG. 55

FIG. 56

FIG. 57

FIG. 58

FIG. 59

FIG. 60

FIG. 61

FIG. 62

FIG. 63

FIG. 64

FIG. 65

FIG. 66

FIG. 67

FIG. 68

FIG. 69

FIG. 70

FIG. 71

FIG. 72

FIG. 73

FIG. 74

FIG. 75

FIG. 76

FIG. 77

FIG. 78

FIG. 79

FIG. 80

FIG. 81

FIG. 82

FIG. 83

FIG. 84

FIG. 85

FIG. 86

FIG. 87

FIG. 88

FIG. 89

FIG. 90

FIG. 91

FIG. 92

FIG. 93

FIG. 94

FIG. 95

FIG. 96

FIG. 97

FIG. 98

FIG. 99

FIG. 100

FIG. 101

FIG. 102

FIG. 103

FIG. 104

FIG. 105

FIG. 106

FIG. 107

FIG. 108

FIG. 109

FIG. 110

FIG. 111

FIG. 112

FIG. 113

FIG. 114

FIG. 115

FIG. 116

FIG. 117

FIG. 118

FIG. 119

FIG. 120

FIG. 121

FIG. 122

FIG. 123

FIG. 124

FIG. 125

FIG. 126

FIG. 127

FIG. 128

FIG. 129

FIG. 130

FIG. 131

FIG. 132

FIG. 133

FIG. 134

FIG. 135

FIG. 136

FIG. 137

FIG. 138

FIG. 139

FIG. 140

FIG. 141

FIG. 142

FIG. 143

FIG. 144

FIG. 145

FIG. 146

FIG. 147

FIG. 148

FIG. 149

FIG. 150

FIG. 151

FIG. 152

FIG. 153

FIG. 154

FIG. 155

FIG. 156

FIG. 157

FIG. 158

FIG. 159

FIG. 160

FIG. 161

FIG. 162

FIG. 163

FIG. 164

FIG. 165

FIG. 166

FIG. 167

FIG. 168

FIG. 169

FIG. 170

FIG. 171

FIG. 172

FIG. 173

FIG. 174

FIG. 175

FIG. 176

FIG. 177

FIG. 178

FIG. 179

FIG. 180

FIG. 181

FIG. 182

FIG. 183

FIG. 184

FIG. 185

FIG. 186

FIG. 187

FIG. 188

FIG. 189

FIG. 190

FIG. 191

FIG. 192

FIG. 193

FIG. 194

FIG. 195

FIG. 196

FIG. 197

FIG. 198

FIG. 199

FIG. 200

FIG. 201

FIG. 202

FIG. 203

FIG. 204

FIG. 205

FIG. 206

FIG. 207

FIG. 208

FIG. 209

FIG. 210

FIG. 211

FIG. 212

FIG. 213

FIG. 214

FIG. 215

FIG. 216

FIG. 217

FIG. 218

FIG. 219

FIG. 220

FIG. 221

FIG. 222

FIG. 223

FIG. 224

FIG. 225

FIG. 226

FIG. 227

FIG. 228

FIG. 229

FIG. 230

FIG. 231

FIG. 232

FIG. 233

FIG. 234

FIG. 235

FIG. 236

FIG. 237

FIG. 238

FIG. 239

FIG. 240

FIG. 241

FIG. 242

FIG. 243

FIG. 244

FIG. 245

FIG. 246

FIG. 247

FIG. 248

FIG. 249

FIG. 250

FIG. 251

FIG. 252

FIG. 253

FIG. 254

FIG. 255

FIG. 256

FIG. 257

FIG. 258

FIG. 259

FIG. 260

FIG. 261

FIG. 262

FIG. 263

FIG. 264

FIG. 265

FIG. 266

FIG. 267

FIG. 268

FIG. 269

FIG. 270

FIG. 271

FIG. 272

FIG. 273

FIG. 274

FIG. 275

FIG. 276

FIG. 277

FIG. 278

FIG. 279

FIG. 280

FIG. 281

FIG. 282

FIG. 283

FIG. 284

FIG. 285

FIG. 286

FIG. 287

FIG. 288

FIG. 289

FIG. 290

FIG. 291

FIG. 292

FIG. 293

FIG. 294

FIG. 295

FIG. 296

FIG. 297

FIG. 298

FIG. 299

FIG. 300

FIG. 301

FIG. 302

FIG. 303

FIG. 304

FIG. 305

FIG. 306

FIG. 307

FIG. 308

FIG. 309

FIG. 310

FIG. 311

FIG. 312

FIG. 313

FIG. 314

FIG. 315

FIG. 316

FIG. 317

FIG. 318

FIG. 319

FIG. 320

FIG. 321

FIG. 322

FIG. 323

FIG. 324

FIG. 325

FIG. 326

FIG. 327

FIG. 328

FIG. 329

FIG. 330

FIG. 331

FIG. 332

FIG. 333

FIG. 334

FIG. 335

FIG. 336

FIG. 337

FIG. 338

FIG. 339

FIG. 340

FIG. 341

FIG. 342

FIG. 343

FIG. 344

FIG. 345

FIG. 346

FIG. 347

FIG. 348

FIG. 349

FIG. 350

FIG. 351

FIG. 352

FIG. 353

FIG. 354

FIG. 355

FIG. 356

FIG. 357

FIG. 358

FIG. 359

FIG. 360

FIG. 361

FIG. 362

FIG. 363

FIG. 364

FIG. 365

FIG. 366

FIG. 367

FIG. 368

FIG. 369

FIG. 370

FIG. 371

FIG. 372

FIG. 373

FIG. 374

FIG. 375

FIG. 376

FIG. 377

FIG. 378

FIG. 379

FIG. 380

FIG. 381

FIG. 382

FIG. 383

FIG. 384

FIG. 385

FIG. 386

FIG. 387

FIG. 388

FIG. 389

FIG. 390

FIG. 391

FIG. 392

FIG. 393

FIG. 394

FIG. 395

FIG. 396

FIG. 397

FIG. 398

FIG. 399

FIG. 400

FIG. 401

FIG. 402

FIG. 403

FIG. 404

FIG. 405

FIG. 406

FIG. 407

FIG. 408

FIG. 409

FIG. 410

FIG. 411

FIG. 412

FIG. 413

FIG. 414

FIG. 415

FIG. 416

FIG. 417

FIG. 418

FIG. 419

FIG. 420

FIG. 421

FIG. 422

FIG. 423

FIG. 424

FIG. 425

FIG. 426

FIG. 427

FIG. 428

FIG. 429

FIG. 430

FIG. 431

FIG. 432

FIG. 433

FIG. 434

FIG. 435

FIG. 436

FIG. 437

FIG. 438

FIG. 439

FIG. 440

FIG. 441

FIG. 442

FIG. 443

FIG. 444

FIG. 445

FIG. 446

FIG. 447

FIG. 448

FIG. 449

FIG. 450

FIG. 451

FIG. 452

FIG. 453

FIG. 454

FIG. 455

FIG. 456

FIG. 457

FIG. 458

FIG. 459

FIG. 460

FIG. 461

FIG. 462

FIG. 463

FIG. 464

FIG. 465

FIG. 466

FIG. 467

FIG. 468

FIG. 469

FIG. 470

FIG. 471

FIG. 472

FIG. 473

FIG. 474

FIG. 475

FIG. 476

FIG. 477

FIG. 478

FIG. 479

FIG. 480

FIG. 481

FIG. 482

FIG. 483

FIG. 484

FIG. 485

FIG. 486

FIG. 487

FIG. 488

FIG. 489

FIG. 490

FIG. 491

FIG. 492

FIG. 493

FIG. 494

FIG. 495

FIG. 496

FIG. 497

FIG. 498

FIG. 499

FIG. 500

FIG. 501

FIG. 502

FIG. 503

FIG. 504

FIG. 505

FIG. 506

FIG. 507

FIG. 508

FIG. 509

FIG. 510

FIG. 511

FIG. 512

FIG. 513

FIG. 514

FIG. 515

FIG. 516

FIG. 517

FIG. 518

FIG. 519

FIG. 520

FIG. 521

FIG. 522

FIG. 523

FIG. 524

FIG. 525

FIG. 526

FIG. 527

FIG. 528

FIG. 529

FIG. 530

FIG. 531

FIG. 532

FIG. 533

FIG. 534

FIG. 535

FIG. 536

FIG. 537

FIG. 538

FIG. 539

FIG. 540

FIG. 541

FIG. 542

FIG. 543

FIG. 544

FIG. 545

FIG. 546

FIG. 547

FIG. 548

FIG. 549

FIG. 550

FIG. 551

FIG. 552

FIG. 553

FIG. 554

FIG. 555

FIG. 556

FIG. 557

FIG. 558

FIG. 559

FIG. 560

FIG. 561

FIG. 562

FIG. 563

FIG. 564

FIG. 565

FIG. 566

FIG. 567

FIG. 568

FIG. 569

FIG. 570

FIG. 571

FIG. 572

FIG. 573

FIG. 574

FIG. 575

FIG. 576

FIG. 577

FIG. 578

FIG. 579

FIG. 580

FIG. 581

FIG. 582

FIG. 583

FIG. 584

FIG. 585

FIG. 586

FIG. 587

FIG. 588

FIG. 589

FIG. 590

FIG. 591

FIG. 592

FIG. 593

FIG. 594

FIG. 595

FIG. 596

FIG. 597

FIG. 598

FIG. 599

FIG. 600

FIG. 601

FIG. 602

FIG. 603

FIG. 604

FIG. 605

FIG. 606

FIG. 607

FIG. 608

FIG. 609

FIG. 610

FIG. 611

FIG. 612

FIG. 613

FIG. 614

FIG. 615

FIG. 616

FIG. 617

FIG. 618

FIG. 619

FIG. 620

FIG. 621

FIG. 622

FIG. 623

FIG. 624

FIG. 625

FIG. 626

FIG. 627

FIG. 628

FIG. 629

FIG. 630

FIG. 631

FIG. 632

FIG. 633

FIG. 634

FIG. 635

FIG. 636

FIG. 637

FIG. 638

FIG. 639

FIG. 640

FIG. 641

FIG. 642

FIG. 643

FIG. 644

FIG. 645

FIG. 646

FIG. 647

FIG. 648

FIG. 649

FIG. 650

FIG. 651

FIG. 652

FIG. 653

FIG. 654

FIG. 655

FIG. 656

FIG. 657

FIG. 658

FIG. 659

FIG. 660

FIG. 661

FIG. 662

FIG. 663

FIG. 664

FIG. 665

FIG. 666

FIG. 667

FIG. 668

FIG. 669

FIG. 670

FIG. 671

FIG. 672

FIG. 673

FIG. 674

FIG. 675

FIG. 676

FIG. 677

FIG. 678

FIG. 679

FIG. 680

FIG. 681

FIG. 682

FIG. 683

FIG. 684

FIG. 685

FIG. 686

FIG. 687

FIG. 688

FIG. 689

FIG. 690

FIG. 691

FIG. 692

FIG. 693

FIG. 694

FIG. 695

FIG. 696

FIG. 697

FIG. 698

FIG. 699

FIG. 700

FIG. 701

FIG. 702

FIG. 703

FIG. 704

FIG. 705

FIG. 706

FIG. 707

FIG. 708

FIG. 709

FIG. 710

FIG. 711

FIG. 712

FIG. 713

FIG. 714

FIG. 715

FIG. 716

FIG. 717

FIG. 718

BIG-1150-99

Grease Interceptor Calculation:
Per Florida Plumbing Code Section
1003.3.4, in accordance with PDI G101
Sec.8.3.1 sizing method based on pipe
diameter and slope table:

Minimum Slope	Pipe Size	GPM 2 minutes drain
1/8" per ft	4"	75

Seats X Turns X Grease Product X POF = Grease Capacity

Number of Seats	Turns per Seat	Meals per Day	Grease Production per Meal (lbs)	POF (Days)	Grease Capacity Needed (LBS)	Description
44	4	400	0.0325	30	390	Eat-In
		400	0.0325	90	1170	Eat-In
		200	0.0325	90	600	y
Total Grease Capacity Needed					1170	

IAPMO RESEARCH AND TESTING, INC.

500 E. Philadelphia Street, Ontario, CA 91761 • Phone (909) 472-4100 • Fax (909) 472-4244 • www.iapmo.com



CERTIFICATE OF LISTING



IAPMO Research and Testing, Inc. is a product certification body in which its product certification system includes inspection and testing of samples taken from the supplier's stock or from the market or a combination of both to verify compliance to the requirements of applicable codes and standards. This activity is coupled with periodic surveillance of the supplier's factory and/or warehouses as well as the assessment of the supplier's quality assurance system. This listing is subject to the conditions set forth in the certification below and is not to be construed as any recommendation, assurance or guarantee by IAPMO Research and Testing, Inc. of the product acceptance by authorities having jurisdiction.

Issued To:

MIFAB, INC.

1501 WEST 110TH STREET CHICAGO, IL 60642, United States

Product:

Hydromechanical Grease Interceptors

Products are in compliance with the following code(s):

Uniform Plumbing Code (UPC)

Products are certified to the following standard(s):

ASME A112.14.3-2015 / CSA B401.1

File Number: 1380

Revised Date: May 13, 2015

Effective Date: February 2024

Valid After: February 2029*

Tim Collins
Chairman, Product Certification Committee



John Miller
Chief Technical Service Officer

NOTE:

1. All grease traps and solid interceptors can be cleaned at any time.
2. "Area for interceptors only"
3. No cars can park on top of them.

GREASE TRAP SCOP OF WORK:

1. Connect New Fixtures and the new grease lines to BIG-1150-99 at 75 GPM.
2. Waste water Sample Port model # SAMPORT
3. Settler BIG-1150-99 with H2O rated pickable cast iron covers.
4. To comply with FOG 2.5 RER-DERM requirements.
5. Adjust pipe to meet existing elevation of main sanitary drain

FOG.2.5.RER-DERM

Required Information	Total
Sample Port	SAMPORT
Capacity (Gallons)	300
FOG load capacity (lbs) at 99% efficiency	1811
Manufacturer	MIFAB
Model #	BIG-1150-99
3rd party certifier	ASME
Interceptor Monitor Alarm (model#)	HLA2
Interceptor Monitor Device (model#)	BY OTHERS
Solid Separator (model#)	BIG-140-S

NOTE:

Sample port shall always be accessible without having to remove merchandise and without standing water, on ground level with minimum 36 inches horizontal clearance from any wall, fixed equipment or stored materials and a minimum of 48 inches vertical clearance from any stored materials or fixed equipment. Grease interceptor shall always be accessible to allow for maintenance and cleaning without any impediments.

BIG-1150-99 meets the DERM 99% efficiency and PH of 3	Model #	Quantity	Flow (GPM)	Grease capacity Needed (lbs)
ASME A 112.14.3, Type D	BIG-1150-99	1	75	18.11

NOTE:

MIFAB interceptors will have access for cleaning the tanks from 72" above.

No.	Test	Clear	Seconds	Rate (GPM)	Lb. Added	Lb. Skimmed	Lb. Retained	Efficiency	Lb. Added	Lb. Skimmed	Lb. Retained	Efficiency
115	1	2	109.75	77.90	15.00	0.345	14.655	97.70%	1725.00	15.845	1709.16	99.08%
116	2	1	112.44	76.04	15.00	0.285	14.715	98.10%	1740.00	16.130	1723.87	99.07%
117	1	2	112.85	76.13	15.00	0.410	14.590	97.27%	1755.00	16.540	1738.46	99.06%
118	2	1	111.93	76.13	15.00	0.315	14.685	97.90%	1770.00	16.855	1753.15	99.05%
119	1	2	112.57	76.13	15.00	0.335	14.665	97.77%	1785.00	17.190	1767.81	99.04%
120	2	1	110.71	76.13	15.00	0.320	14.680	97.87%	1800.00	17.510	1782.49	99.03%
121	1	2	112.97	76.13	15.00	0.310	14.690	97.93%	1815.00	17.820	1797.18	99.02%
122	2	1	110.58	76.13	15.00	0.295	14.705	98.03%	1830.00	18.115	1811.89	99.01%
123	1	2	109.75	76.13	15.00	3.290	11.710	78.07%	1845.00	21.405	1823.60	98.84%
124	1	2	112.44	76.13	15.00	0.490	14.510	96.73%	1860.00	21.895	1838.11	98.82%

Satisfies Miami DERM 99% efficiency requirements.
Product labels are permanently attached to inside and outside of unit for easy viewing.



BIG-1150-99

Seats X Turns X Grease Product X POF = Grease Capacity

Number of Seats	Turns per Seat	Meals per Day	Grease Production per Meal (lbs)	POF (Days)	Grease Capacity Needed (LBS)	Description
11	1	400	0.0325	30	390	Eat-In
		400	0.0325	90	1170	Take-Out
		200	0.0325	30	650	Bakery
Total Grease Capacity Needed					1810	

FOG 2.5 RER-DERM

Required Information	Total
Sample Port	SAMPORT
Capacity (Gallons)	300
FOG load capacity (lbs) at 99% efficiency	1,811
Manufacturer	MIFAB
Model #	BIG-1150-99
3rd party certifier	ASME
Interceptor Monitor Alarm (model#)	HLA2
Interceptor Monitor Device (model#)	BY OTHERS
Solid Separator (model#)	BIG-140-S

BIG-1150-99 meets the DERM 99% efficiency and PH of 3

ASME A 112.14.3, Type D

Model #

Quantity

Flow (GPM)





Grease capacity Needed (lbs)

BIG-1150-99

1

75

1,811



SAMPORT SPECIFICATION SHEET

