

Location: _____



C1100-S

FLOOR CLEANOUT WITH SQUARE ADJUSTABLE COVER AND PLUG

Specification: MIFAB C1100-S Series adjustable floor cleanout with lacquered cast iron body and anchor flange, secondary "O" ring Test Seal, 4" diameter cleanout opening and square scoriated combined cover and plug top assembly (specify material type) with stainless steel vandal proof allen key screws and primary gasket seal. (For membrane floors, add Suffix -C for the membrane clamp.)

Function: Used in finished floors to provide emergency access to the plumbing lines for removal of blockages. Replacement of the surface level cover/plug with the neoprene gasket glued to the underside provides visual evidence that the cleanout has been properly resealed to prevent harmful sewer gases from entering the building.

COVER ADJUSTMENT

MIN	MAX
1/2"	1 1/4"

COMBINED COVER/PLUG

8" DIAMETER

5" or 6" SQUARE

NEOPRENE PRIMARY GASKET SEAL

"O" RING SECONDARY TEST SEAL

A1 BODY

PIPE SIZE 2", 3", 4", 5", 6"

5" 6"

COVER ADJUSTMENT (SEE CHART)

4" NPSM

"O" RING SECONDARY SEAL

PIPE SIZE (SEE CHART)

Ø8"

BODY HEIGHT (SEE CHART)

SEE BODY HEIGHT CHART BELOW

ANSI/ASME RATING		PARTS	A1 BODY	S-1
COVER	LOAD RATING			
5", 6" SQ. N.B. (-1)	2000-4999 lbs			

*Specify 6S-1 for 6" x 6" part

C1100 MEETS ANSI CLEANOUT STANDARD A112.36.2M-1991 (R2017)
Metric equivalents see chart below. (Dimension) Denotes Millimetres.

TOP ASSEMBLY DIAMETER	TOP ASSEMBLY ADJUSTMENT		ANSI/ASME RATING	PIPE SIZE	BODY HEIGHT						
	MIN	MAX			LOAD RATING		NO HUB (STANDARD)	PUSH ON (P)	THREADED (T)	INSIDE CAULK (X)	PVC/ABS (-30)/(-31)
					N.B. (-1) Lbs.						
5" x 5" (127 x 127)	1/2" (13)	1 1/4" (32)	Up to 4,999	2" (51)	3" (76)	3 3/8" (86)	2 1/4" (57)	3 3/4" (95)	2 5/8" (67)		
6" x 6" (152 x 152)	1/2" (13)	1 1/4" (32)	Up to 4,999	3" (76)	3" (76)	3 3/8" (86)	2 5/8" (67)	3 3/4" (95)	3 1/4" (83)		
				4" (102)	3" (76)	3 3/8" (86)	2 5/8" (67)	3 3/4" (95)	3 1/2" (89)		
				5" (127)	3" (76)	--	2 5/8" (67)	6 7/8" (175)	--		
				6" (152)	3 1/2" (89)	6 7/8" (175)	--	--	--		

Suffix	Description
(Standard)	No hub outlet
-6	Security screws (TR25 Torx & pin)
-11	Acid resistant epoxy coated body
-13	Galvanized body
-28	Stainless steel body (Type 304)
-30	PVC socket connection body
-31	ABS socket connection body
-34	Secondary closure plug

Suffix	Description
-C	Membrane clamp
-P	Push on outlet (2", 3", 4")
-T	Threaded outlet (2", 3", 4")
-X	Inside caulk outlet (2", 3", 4")
-Z	Extended wide elastomeric flange

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: _____ Page No: _____

Section No: _____ Contractor: _____

Schedule No: _____ Purchase Order No: _____