

Location: _____



C1100-TOSS

TOP SET® FLOOR CLEANOUT WITH SQUARE TOP

Specification: MIFAB® Series C1100-TOSS Top Set® floor cleanout with square top cleanout with PVC, ABS or lacquered cast iron body, securing and adjustable hardware, and scoriated combined gasketed nickel bronze cover and plug top assembly with stainless steel allen key screws. Cover can be adjusted vertically and side to side after the pour with 1/2" thick composite protective cover and indicating whisker.

Function: Used in finished floors to provide emergency access to the plumbing lines for removal of blockages. Replacement of the surface level cover/plug with the neoprene gasket glued to the underside provides visual evidence that the cleanout has been properly resealed to prevent harmful sewer gases from entering the building. The patented MIFAB® Top Set® floor cleanout with square top ships complete with a 1/2" thick plastic cover to protect the cleanout during the concrete pour. The installer pours the concrete to the top level of the plastic cap. Channel locks are used to remove the cover after the concrete pour has settled. Then, remove the solid cleanout cover and use a Phillip's head screwdriver to engage the three screws located underneath the cover. Turn the screws the same amount to elevate the cover up to the finished floor. Turn the screws a different amount to tilt the cover to the same angle as the finished floor.

COVER ADJUSTMENT	
MIN	MAX
7/16"	1 9/16"

ANSI/ASME RATING	
COVER	LOAD RATING
5" SQ. N.B. (-1)	2000-4999 lbs
5" SQ. N.B. (-3)	5000-7499 lbs

PARTS	A1 BODY	TOSS-1 or -3	C144(**)

C1100-TOSS MEETS ANSI CLEANOUT STANDARD A112.36.2M-1991 (R2017) (***) Indicates 2, 3 or 4 for plug size.

MODEL NUMBER	C1100-TOSS TOP SET FLOOR CLEANOUT WITH SQUARE TOP			PIPE SIZE	A1 BODY HEIGHT				
	WT. Lbs	COVER SIZE	OUTLET SIZE		NO HUB (STANDARD)	PUSH ON (P)	THREADED (T)	INSIDE CAULK (X)	PVC/ABS (-30)/(-31)
C1102-TOSS	7.25	5" x 5"	2"	2" (51)	3" (76)	3 3/8" (86)	2 1/4" (57)	3 3/4" (95)	2 5/8" (66.7)
C1103-TOSS	7.00	5" x 5"	3"	3" (76)	3" (76)	3 3/8" (86)	2 5/8" (67)	3 3/4" (95)	3 1/4" (82.5)
C1104-TOSS	6.90	5" x 5"	4"	4" (102)	3" (76)	3 3/8" (86)	2 5/8" (67)	3 1/2" (89)	3 1/2" (89)
C1105,6-TOSS	8.50	5" x 5"	5", 6"	5" (127)	3" (76)	-	2 5/8" (67)	6 7/8" (175)	-
				6" (152)	3 1/2" (89)	6 7/8" (175)	-	-	-

SUFFIX	OPTIONAL VARIATIONS
-6	Security screws (TR25 Torx & pin) (H-1039A)
-11	Acid resistant epoxy coated body
-13	Galvanized body
-28	Stainless steel body (Type 304) (2", 3", 4" No Hub Only)
-30	PVC socket connection body* (2", 3", 4")
-31	PVC socket connection body* (2", 3", 4")
-34	T-cone plug and gasket (2", 3", 4")(C1440 Series)

SUFFIX	OPTIONAL VARIATIONS
-95	Client logo (-3 only)
-C	Membrane clamp (A1-C1)
-NH	No hub outlet
P	Push on outlet (2", 3", 4")*
T	Threaded outlet (2", 3", 4")
X	Inside caulk outlet (2", 3", 4")
-Z	Extended wide flange on body (13" dia. x 1/8" thick)

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: _____	Page No: _____
Section No: _____	Contractor: _____
Schedule No: _____	Purchase Order No: _____