

CB

BRIDGE SUPPORT SERIES W/ TWO CX SERIES SUPPORTS AND 1 5/8" GALVANIZED CHANNEL

Specification:

Two (2) Bases Bridged with 14 gauge Galvanized Channel (1 5/8" high) **Dimensions** - 5 5/8" High x 6" Wide x Bridge Length (Overall Length)

Material - 100% recycled rubber, UV resistant

Load Rating - Each base rated at 500 lbs. Refer to beam load of channel at various lengths as other factor (see Strut catalog)

and many other applications. It is UV resistant and suitable for installation on most types of roofing material or other flat surfaces.

Environmentally Friendly made from 100% recycled tires



Consult with roofing consultant for allowable loads.

Function: CB Bridge channel is designed as a superior sleeper for HVAC equipment, cable tray, roof walkway systems, refrigeration equipment


U.S. Patent No. 7,866,093




CB10-28 illustrated



Pipe clamp by others





Strut Clamps sold separately.

*H1 - Overall height is from bottom of rubber support to top of the strut

**H2 - Base height is from bottom of rubber support to top of the rubber support Channel also available in corrosion resistant stainless steel or aluminum.

MODEL NO.	OVERALL HEIGHT (H1)*	HEIGHT (H2)**	CURB LENGTH (L)	STRUT LENGTH (L)	WEIGHT
CB10-28	5 5/8" (143)	4" (102)	9.6" (244)	28" (711)	13.59 lbs.
CB10-36	5 5/8" (143)	4" (102)	9.6" (244)	36" (914)	14.88 lbs.
CB10-42	5 5/8" (143)	4" (102)	9.6" (244)	42" (1067)	15.66 lbs.
CB10-50	5 5/8" (143)	4" (102)	9.6" (244)	50" (1270)	17.24 lbs.
CB10-60	5 5/8" (143)	4" (102)	9.6" (244)	60" (1524)	18.79 lbs.

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name:	Page No:	
Section No:	Contractor:	
Schedule No:	Purchase Order No:	
		

MIFAB® reserves the right to make changes in material and design without formal notice and obligation.

USA: 1-800-465-2736 www.mifab.com CAN: 1-800-387-3880