

DS Series

DUCT SUPPORT SERIES

Specification: The DS Duct Support Series is designed specifically for HVAC ductwork. The fixed dimensions give the ability for quick install times. The double C-Ports (C20) provide added support and are made of 100% recycled rubber. The DS Series also come equipped with 4-hole 90-degree fittings for added crossbeam support and 8 hold wing fittings to connect the uprights to the C-port bases.

DS Duct Support Series

Material

Base : 100% recycled rubber, UV resistant

Strut : 14-gauge galvanized channel strut (1 5/8" high)

Uprights and crossbeam: 12-gauge slotted strut (1 5/8" x 1 5/8")

Warranty : 10 years

Recommended Spacing: Refer to local code

Crossbeam: Dimensions -24" (See chart)Maximum load: DS -1,200 lbs., DSW -1,500 lbs.

May qualify for L.E.E.D. credits





Consult with roofing consultant for allowable loads.

Function: The DS Series is designed to provide support specifically for ductwork. The crossbeam has the ability to be moved up or down the vertical supports. The bases feature an 8-hole wing fitting for added stability. Widebody bases are used with the DSW Series.



Model No. (SKU)	Crossbeam Width	Crossbeam Height	Base Width (W)	Base Length (L)	Weight
DS20-3624	24" (610)	Up to 36" (914)	6" (152)	19.2" (488)	37.0 lbs.
DS20-3640	40" (1016)	Up to 36" (914)	6" (152)	19.2" (488)	39.2 lbs.
DS20-4840	40" (1016)	Up to 48" (1219)	6" (152)	19.2" (488)	42.5 lbs.

Uprights are not included. Strut can be cut to suit job site. Channel also available in corrosion resistant stainless steel or aluminum.

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name:	Page No:	
Section No:	Contractor:	
Schedule No:	Purchase Order No:	

MIFAB® reserves the right to make changes in material and design without formal notice and obligation.

USA: 1-800-465-2736 www.mifab.com CAN: 1-800-387-3880