

Location: _____




F1640

ISOLATION FLOOR DRAIN WITH 9" ADJUSTABLE STRAINER TRACTOR GRATE

Specification: MIFAB® Series F1640, 9" (229) diameter blood and water drain set consisting of two lacquered cast iron bodies with anchor flange and weepholes. One body furnished with a 9" (229) diameter lacquered cast iron adjustable top assembly and special duty ductile iron grate. The other body furnished with a solid gasketed ductile iron cover with lift ring. The top assemblies are interchangeable with either body. (For membrane floors, add Suffix -C for the membrane clamp.)

Function: Used in packing house slaughtering areas. The slotted grate drain permits drainage of blood to a separate holding tank while the gasketed covered drain adjacent is connected to the sewer. The gasketed cover is to be removed and placed into the drain holding slotted grate during washdown, and the slotted grate is to be placed into the drain previously holding the gasketed cover. This is to ensure that water used in the cleaning operation will be directed to the sewer and not to the blood storage tank.



STRAINER DIAMETER	STRAINER ADJUSTMENT		FREE AREA	ANSI/ASME RATING LOAD RATING S.S. (-3) / D.I. (-4) ANSI/ASME LOAD CLASS "SPECIAL DUTY" (OVER 10,000 LBS.)	PIPE SIZE	BODY HEIGHT				
	MIN	MAX				NO HUB (STANDARD)	PUSH ON (P)	THREADED (T)	INSIDE CAULK (X)	PVC/ABS (-30)/(-31)
9" (229)	1 3/4" (45)	2 5/8" (67)	18 in ² (11,613 ²)		2" (51)	3" (76)	3 3/8" (86)	2 1/4" (57)	3 3/4" (95)	2 15/16" (75)
					3" (76)	3" (76)	3 3/8" (86)	2 5/8" (67)	3 3/4" (95)	3 3/4" (95)
					4" (102)	3" (76)	3 3/8" (86)	2 5/8" (67)	3 3/4" (95)	3 3/4" (95)
					5" (127)	3" (76)	—	2 5/8" (67)	3 3/4" (95)	—
					6" (152)	3 1/4" (83)	6 1/2" (165)	—	—	—

- SUFFIX OPTIONAL VARIATIONS**
- 3 Stainless steel strainer (vener) and cover
 - 4 Ductile iron strainer
 - 5 Sediment bucket
 - 6 Security screws (T-20 Torx & pin)
 - 7 1/2" trap seal primer connection
 - 8 Backwater valve (2", 3", 4")
 - 11 Acid resistant epoxy coated body
 - 13 Galvanized body
 - 15 Extension
 - 21 Secondary flat stainless steel strainer (2", 3", 4")
 - 28 Stainless steel body (Type 304)
 - 30 PVC socket connection body
 - 31 ABS socket connection body
 - 34 Closure plug
 - 40 Underdeck clamp

- SUFFIX OPTIONAL VARIATIONS**
- 41 Sump receiver
 - 90 Threaded side outlet (2", 3", 4")
 - 90NH No hub side outlet (2", 3", 4")
 - 95 Client logo
 - BA Minimum 51% material cost made in the USA
 - C Membrane Clamps
 - C1 Clamp rings for low rough-in (min. 1/2" (13))
 - HP Heel proof grate (1/4" maximum grate opening size, -3 only)
 - J 6" x 3" x 1" funnel
 - (Standard) No hub outlet
 - MG MI-GARD Floor Drain Trap Sealer (2", 3" or 4")
 - P Push on outlet
 - PA Pennsylvania Steel Act compliant product
 - T Threaded outlet (2", 3", 4")
 - X Inside caulk outlet
 - Z Extended wide elastomeric flange

Job Name: _____ Page No: _____

Section No: _____ Contractor: _____

Schedule No: _____ Purchase Order No: _____