

Location: _____



FS1730-FL

12" X 12" X 8" FLOOR AREA & INDIRECT SANITARY WASTE DRAIN WITH FLANGE

Specification: MIFAB Series FS1730-FL, 12" x 12" x 8" deep cast iron floor area and indirect sanitary waste drain complete with white acid resistant porcelain enamel coated interior, light duty loose set grate and anchor flange with weepholes. Anti-splash aluminum dome strainer included.

Function: Used in kitchens, restaurants, grocery stores, hospitals, schools, and other areas that require a large volume sanitary drain. Also suitable for indirect waste applications. The anchor flange is engineered to receive water proofing membrane. Membrane clamps are recommended for use with the anchor flange (Suffix -C).

A.R.E. LOOSE SET GRATE
MEMBRANE CLAMPS (4)
2 x (FS1700-PCS)
2 x (FS1700-PCL)

FULL GRATE ILLUSTRATED (STANDARD)

9.31" ANCHOR FLANGE (14 1/2" x 14 1/2")

12" WEEP HOLE

HARDWARE (8) x (H-10)

POLY DOME STRAINER (FS1500-PD) (INCLUDED)

2", 3", 4" OUTLET

WHITE ACID RESISTANT PORCELAIN ENAMEL (A.R.E.) COATING ON INSIDE OF CAST IRON BODY

2" BODY HEIGHT
SEE BODY HEIGHT CHART 1

8"

*ADD 3/4" TO DIMENSION AND 1/2" TO HEIGHT FOR NB, SS FRAME & GRATE

FS1730-FL PARTS

Note: Specify outlet size and connection type.
Dome strainer included with body.

(*) Specify 150 for 1/2 grate, 175 for 3/4 grate or nothing for full grate
Note: For Nickel Bronze or Stainless Steel grate and frame, specify -TA instead of -PG and specify -1 for Nickel Bronze and -3 for Stainless Steel

FS1730T-FL (Transition Body) PARTS

Note: Specify outlet size and connection type.
Dome strainer included with body.

PIPE SIZE	BODY HEIGHT				
	NO HUB (STANDARD)	PUSH ON (P)	INSIDE CAULK (X)	THREADED (T)	PVC (-30) / ABS (-31)
2" (51)	9 3/4" (248)	9 3/4" (248)	*12" (305)	*10 1/2" (267)	*11 1/4" (286)
3" (76)	9 3/4" (248)	9 3/4" (248)	10 5/8" (270)	*10 7/8" (276)	*11 1/4" (286)
4" (102)	9 3/4" (248)	9 3/4" (248)	10 5/8" (270)	*10 7/8" (276)	*11 1/4" (286)

*Indicates outlet size and connection available with transition outlet body only. Outlet sizes indicated by the * are available with the transition outlet body only

Suffix	Description
-1	Nickel bronze strainer
-3	Stainless steel strainer
-5	Sediment bucket (FS1700-PB)
-6	Security screws (H-1039A, 4 pcs) (-1, -3 only)
-7	Trap seal primer connection
-8	Backwater Valve (BV1250 Series) (2", 3", 4")
-9	Hinged grate (-3 only)
-21	Secondary flat strainer (FD-9600 Series)
-22	Less Enamel Cast Iron grate (deduct)
-22	Less Nickel Bronze grate (deduct)
-22	Less Stainless Steel grate (deduct)
-30	PVC socket connection W/A.R.E. Body (2", 3", 4")
-31	ABS socket connection W/A.R.E. body (2", 3", 4")
-32	Deep seal trap (2", 3", 4" no hub) (MI-950 Series)
-51	2 1/2" round center grate opening (-1, -3 only)
-69	Stainless Steel Sediment bucket (FS1700-PB-3)-3)
-83	Stainless steel mesh screen over sediment bucket

-150	Half grate
-175	3/4 grate
-C	Membrane clamp (add to FS1730-FL only)
-P	Push on outlet
-T	Threaded outlet
X	Inside caulk outlet

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: _____ Page No: _____
 Section No: _____ Contractor: _____
 Schedule No: _____ Purchase Order No: _____