

Location: \_\_\_\_\_



**MC-34**

**SINGLE HANGER PLATE AND EXPOSED  
ARM LAVATORY CARRIER WITH TWO UPRIGHTS**

**Specification:** MIFAB® Series MC-34 single hanger plate and exposed arm lavatory carrier with universal, adjustable, top support plate and white lacquered, adjustable, cast iron exposed support arms assembled to lacquered cast iron invertible and adjustable arm supporting brackets. Complete with two lacquered 2" x 1" x 1/8" thick structural steel uprights with 3" x 4 1/2" welded steel feet and mounting hardware.

**Function:** Used to support heavy duty wall-hung lavatories that are independent of the wall. Heavy duty cast iron support arms provide extra support for the fixture. Designed for use in conjunction with the fixture hanger plate supplied by the fixture manufacturer.

**CUTOUT FOR FIXTURE WITH BACK SUPPLY**

**1/4" x 8" ALL THREADED PLATED RODS (6 PIECES) W / HARDWARE**

**SINGLE UNIVERSAL PLATE ASSEMBLY, SECURED TO UPRIGHTS WITH "U" BOLTS TO PROVIDE EASE OF ROUGH-IN HEIGHT ADJUSTMENT**

**(1/4"-20 x 8" ALL THREADED PLATED RODS (6 PIECES) W / HARDWARE**

**15 3/4"**

**36"**

| ADJ. RANGE |        |
|------------|--------|
| MIN        | MAX    |
| 1 1/4"     | 4 7/8" |

**EXTRA HEAVY RECTANGULAR STEEL STRUCTURAL UPRIGHTS (2" x 1" x 1/8" Wall Thickness)**

**HEAVY DUTY WELDED FEET THAT FIT WITHIN STANDARD STUD WALL CONSTRUCTION**

**3"**

**4 1/2"**

**WHITE LACQUERED CAST IRON EXPOSED SUPPORT ARM**

**MC-34 Series Meets ANSI/ASME fixture carrier standard A112.6.1M-97**

**NOTE: FOOT SUPPORTS SHOULD BE SECURELY ANCHORED TO FLOOR WITH 1/2" (13) BOLTS AND ANCHORS BY OTHERS.**

**Note: See the various fixture dimensional rough-in guides on the [www.mifab.com](http://www.mifab.com) website.**

**17" (432)**

**2.75" (69.9)**

**(4) 1/4" STUDS**

**36"**

**FINISHED FLOOR**

**BASE DETAIL**

**2.8" (71.1)**

**3" (76.2)**

**1.8" (45.7)**

**4.5" (114.3)**

**0.5" (12.7)**

**1.5" (38)**

**2" MIN., 5" MAX.**

**SINK**

**15 3/4"**

**WHITE LACQUERED CAST IRON**

**ADJ. RANGE 1 1/4" MIN, 4 7/8" MAX**

**FINISHED SURFACES**

**1" x 2" RECT. TUBE**

**STEEL PLATE WELDED TO UPRIGHT**

| SUFFIX | OPTIONAL VARIATIONS                                            |
|--------|----------------------------------------------------------------|
| -A     | Stud length over 8" (specify)                                  |
| -BA    | Minimum 51% material cost made in the USA                      |
| -G     | Wall support plate                                             |
| -HDH   | Heavy duty hanger                                              |
| -PA    | Pennsylvania Steel Act compliant product                       |
| -PFAB  | Prefabricated carrier                                          |
| -SL    | 3/4" Slots in legs – to receive 1/2" water piping through legs |
| -Z     | Higher uprights (over 36")                                     |
| -14    | Vandal proof finish trim                                       |
| -88    | 3/8" threaded eye bolts for cast iron lavs (H-1028)            |

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: \_\_\_\_\_ Page No: \_\_\_\_\_

Section No: \_\_\_\_\_ Contractor: \_\_\_\_\_

Schedule No: \_\_\_\_\_ Purchase Order No: \_\_\_\_\_