

Location: _____



MI-FLEX-CLAY

**FLEXIBLE COUPLINGS
CLAY TO CLAY**




Specification: MIFAB® Series MI-FLEX-CLAY (specify size) of flexible rubber couplings are manufactured from neoprene compound that meets the requirements of ASTM C564 and stainless steel clamps tightened with 5/16" Type 300 stainless steel hex head screws. MI-FLEX Series of flexible couplings are tested and certified to ASTM Standard C1173 and CSA Standard B602 and listed with IAPMO.

Function: MIFAB's MI-FLEX-CLAY Series of flexible rubber couplings are used to connect clay pipe to clay pipe. For couplings with two bands, tighten 1-2, alternately until minimum 60 inch lbs. of torque is attained for each band. Tested to maintain 4.3 p.s.i. maximum line pressure (10' head pressure). All models conform to the National Plumbing Code of Canada and are manufactured in compliance with ASTM #C1173 and CSA B602 Standards. Non constant temperature rating is 140 F. Stainless Steel.

Material Specifications:

- Bands** – Type 300 AISI stainless steel (Minimum tensile 165,000 psi).
- Gasket** – Elastomeric compound that meets the requirements of ASTM C-564.
- Screw Housing** – Type 300 AISI stainless steel.
- Screw** – Type 300 AISI stainless steel, 5/16" Hex head / Shoulder.



MI-FLEX-400 illustrated

MODEL NUMBER	PIPE SIZE	A	B	C HEIGHT
MI-FLEX-CLAY-600	6" Clay x 6" Clay	7.50" (191)	7.50" (191)	6" (152)
MI-FLEX-CLAY-1212	12" Clay x 12" Clay	14.51" (369)	14.51" (369)	6.38" (162)
MI-FLEX-CLAY-1515	15" Clay x 15" Clay	19.65" (499)	18.15" (461)	10" (254)

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: _____

Page No: _____

Section No: _____

Contractor: _____

Schedule No: _____

Purchase Order No: _____

MIFAB reserves the right to make changes in material and design without formal notice and obligation.

USA: 1-800-465-2736 www.mifab.com CAN: 1-800-387-3880