

Location: _____



MI-FLEX-AH

**FLEXIBLE COUPLINGS
ADC / HANCOR TO PVC**



Specification: MIFAB® Series MI-HUB-ARC-DI (specify size) shielded repair couplings are manufactured with gaskets made from neoprene compound that meets the requirements of ASTM C564 housed inside a Type 300 stainless steel shield. Two Type 300 stainless steel clamps tightened with 5/16" Type 300 stainless steel hex head screws surround the shield to provide the sealing force. The MI-HUB-ARC Series of shielded repair couplings are tested and certified to ASTM Standard C1173 and CSA Standard B602 and listed with IAPMO. All models are listed to the National Plumbing Code of Canada and relevant Canadian Standard(s) and bear the cUPC mark of conformity. Non constant temperature rating is 140 F.

Function: MIFAB's MI-HUB-ARC-DI Series of shielded repair couplings are engineered for resistance to heavy earth loads and shear forces and also provide improved pipe alignment. For asbestos cement or ductile iron pipe to cast iron or plastic pipe. For couplings with two bands, tighten 1-2, couplings with four bands, tighten 2-3-1-4 and couplings with six bands, tighten 3-2-1-4-5-6 alternately until minimum 60 inch lbs. of torque is attained for each band. Tested to maintain 4.3 p.s.i. maximum line pressure (10' head pressure) Tested and Certified to ASTM Standard #C1173. All models are listed with I.A.P.M.O. (U.P.C.) 5/16" driver required to tighten bolts. All models are listed to the National Plumbing Code of Canada and relevant Canadian Standard(s) and bear the cUPC mark of conformity. All models are manufactured in compliance with ASTM #C1173 and CSA B602 Standards. Non constant temperature rating is 140 F. Stainless Steel Clamps and 5/16" hex head bolts are made from Type 300 Stainless Steel.

Material Specifications:

Bands – Type 300 AISI stainless steel (Minimum tensile 165,000 psi).

Gasket – Elastomeric compound that meets the requirements of ASTM C-564.

Screw Housing – Type 300 AISI stainless steel.

Screw – Type 300 AISI stainless steel, 5/16" Hex head / Shoulder.



**MI-HUB-ARC-44, 55, 66
PICTURED**

MODEL NUMBER	PIPE SIZE	A WIDTH	B WIDTH	C HEIGHT
MI-HUB-ARC-DI-88	8" Asbestos Cement / Ductile Iron to 8" CI/PL	8.64" (219)	8.64" (219)	6.04" (153)

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: _____ Page No: _____
 Section No: _____ Contractor: _____
 Schedule No: _____ Purchase Order No: _____

MIFAB reserves the right to make changes in material and design without formal notice and obligation.

USA: 1-800-465-2736 www.mifab.com CAN: 1-800-387-3880