

Location: _____




MI-SAND/OIL

SAND AND OIL INTERCEPTOR

Specification: MIFAB® Series MI-SAND/OIL____ sanitary powder epoxy coated inside and outside fabricated 10 gauge steel sand and oil interceptor with a holding capacity of - see chart below. Interceptor complete with gasketed non-skid powder epoxy coated lid, removable sediment bucket with perforated baffle beside inlet, deep seal trap with integral sewer gas stopper, two 2" vent connections, adjustable oil draw off assembly and no hub inlet/outlet.

Function: Used in service areas to receive wastewater with sand and oil contaminants. Sediment bucket with perforated baffle designed to capture debris and prevent drain line clogging. Integral sewer gas stopper will prevent harmful gases from entering via the outlet. Electrostatically applied powder epoxy coating ensures extra long life.



Metric equivalents see chart below. (Dimension) Denotes Millimetres

Note: The "C" dimension detailed above is from either the middle of the inlet or the outlet to the top the interceptor. The inlet and outlet dimensions are always the same.

MODEL NO.	LIQUID HOLDING CAP. USG	A	B	C	D	E	F	G	NO. OF LIDS	NO. OF BOLTS
MI-SO-0	109	42" (1067)	28" (711)	6" (152)	26" (660)	32" (813)	4" (102)	19" (483)	2	88
MI-SO-1	193	55" (1397)	37" (940)	8" (203)	26" (660)	34" (864)	4" (102)	19" (483)	2	12
MI-SO-2	227	58" (1473)	38" (965)	8" (203)	28" (711)	36" (914)	4" (102)	21" (533)	3	12
MI-SO-3	265	61" (1549)	39" (991)	8" (203)	28" (711)	36" (914)	4" (102)	23" (584)	3	24
MI-SO-4	396	70" (1778)	44" (1118)	10" (254)	34" (864)	44" (1118)	4" (102)	27" (686)	6	24
MI-SO-5	501	75" (1905)	46" (1168)	10" (254)	38" (965)	48" (1219)	4" (102)	31" (787)	6	24
MI-SO-6	580	77" (1956)	49" (1245)	12" (305)	40" (1016)	52" (1321)	6" (152)	32" (813)	6	32
MI-SO-7*	612	80" (2032)	51" (1295)	12" (305)	40" (1016)	52" (1321)	6" (152)	36" (914)	8	32
MI-SO-8*	786	84" (2134)	56" (1422)	14" (356)	44" (1118)	58" (1473)	6" (152)	46" (1168)	8	32
MI-SO-9*	1172	92" (2337)	61" (1549)	14" (356)	54" (1372)	68" (1727)	6" (152)	46" (1168)	8	36
MI-SO-10*	1808	102" (2591)	74" (1880)	14" (356)	62" (1575)	76" (1930)	8" (203)	53" (1346)	9	36
MI-SO-11*	2105	108" (2743)	76" (1930)	14" (356)	66" (1676)	80" (2032)	8" (203)	57" (1448)	9	36

Note: The "A" and "B" dimensions represent the largest dimensions of the interceptor (lid). Since the lid overhangs the body by 1/2" (13) on all sides, deduct 1" (25) from the stated dimensions in the charts below to determine the actual body length and width.

SUFFIX	OPTIONAL VARIATIONS
-AL	Aluminum lid(s)
-AP	Anode pack
-BA	Buy American Act compliant product
-C	Extension "C" as required
-FL	Anchor flange

-FLM	Anchor flange and membrane clamp
-HD	Heavy Duty load rated lids
-HLA	High level alarm
-SS	Stainless steel cover shroud
-T	F.I.P. female threaded inlet and outlet
specify	Special size inlet and outlet

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: _____ Page No: _____
 Section No: _____ Contractor: _____
 Schedule No: _____ Purchase Order No: _____

MIFAB reserves the right to make changes in material and design without formal notice and obligation.

USA: 1-800-465-2736 www.mifab.com CAN: 1-800-387-3880