

Location: _____



R1200-ES

LARGE SUMP ROOF DRAIN WITH EXTENSION FOR 2" - 9" INSULATION WHEN BODY IS POURED INTO THE DECK

Specification: MIFAB® Series R1200-ES lacquered cast iron deep sump roof drain with 15" diameter anchor flange, large cast iron waterproofing membrane clamp ring with integral gravel stop, adjustable extension, and standard self-locking polyethylene dome strainer with a free area of 125 square inches.

Function: Used in any type of flat roofs. Large free area dome provides for efficient drainage of rain water and prevents debris from entering the drain line. Adjustable extension available in various depths to match with insulation. Extra wide anchor flange and membrane clamp with tongue in groove design provides for secure grip of membrane and roof flashing materials.

PARTS

- A2-C3
- A2 BODY
A7 BODY for
10" OUTLET
- A2-PD
- A2-C3-W(*)
(* Specify 4, 6, 8
A7-C3-W10 for
10" outlet
- A2-ES-(*)
(* Specify 4, 6, 8
A7-ES-10 for 10" outlet
- HS-1 (x2)
- W(*)-PN9R
(* Specify
4, 6, 8 or 10

BODY HEIGHT A2 BODY BASED ROOF DRAINS					
PIPE SIZE	NO HUB (STANDARD)	PUSH ON (P)	THREADED "T"	INSIDE CAULK (X)	PVC/ABS (-30/-31)
2" (51)	5 3/4"	5 1/2"	6 1/2"	6 1/2"	6 3/4"
3" (76)	5 3/4"	5 1/2"	6 5/8"	6 1/2"	7 1/2"
4" (102)	5 3/4"	5 1/2"	5 1/2"	6 1/2"	7 5/8"
5" (127)	5 3/4"	-	6 5/8"	6 3/4"	-
6" (152)	7 1/4"	5 5/8"	5 5/8"	6 1/2"	-
8" (203)	5 7/8"	-	-	A7-8X (6 1/2")	-
10" (252) (A7-10NH)	5 5/8"	-	-	-	-

The -ES adjustable extension can be moved up and down in the A2 body (2" - 9") to meet the required insulation thickness on top of the roof deck.

SUFFIX	OPTIONAL VARIATIONS
-6	Vandal proof (Metal dome only)(H-1029)
-11	Acid resistant epoxy coated body, membrane clamp & dome
-12	Galvanized metal dome (add to -M Price)
-12A	Galvanized body and membrane clamp
-12B	Galvanized metal dome and membrane clamp
-13	Galvanized body, membrane clamp and dome
-28	Stainless steel body (Type 304) (2", 3", 4" NH)
-30	PVC socket connection body (2", 3", 4")
-31	ABS socket connection body (2", 3", 4")
-81	Rough bronze dome (A2-MDL-81)
-83	Stainless steel mesh screen over metal dome (A2-SSD)
-90	Threaded side outlet (cast iron only) (2",3",4", 6") (N/A in -30,-31)
-90-NH	No hub side outlet (cast iron only) (2",3",4")(N/A in -30,-
-B	Sump receiver (A2-BP)
-EG	Galvanized adjustable extension
-F	Accuflow (parabolic weir) (adj. to 1, 2 or 3 slots)

-G	Ballast guard (A2-BG)
-M	Cast iron dome
-M-80	Low aluminum dome (4 1/4" high) (A2-MDL-80) (to poly dome)
P	Push on outlet, (2",3",4",6") Specify POG-6 for C.I. pipe and POG-6-PVC for PVC pipe, 2", 3", 4" use same gasket
-R	2" external water dam (A2-WD)
T	Threaded outlet, (2", 3", 4", 5" or 6")
-U	Underdeck clamp (A2-C3) (A368-DC for 8")
-U3	Underdeck clamp with cut away side (A2-C3-C0)
-W	Adjustable water dam (5" high x 4" diameter) (A2-C3-W and W-31)
-W-1	Water proofing flange (A2-W-1)
-W2	2" internal water dam (2" high x 4" diameter) (A2-C3-W and W-31)
-W3	3" internal water dam (3" high x 4" diameter) (A2-C3-W and W-31)
-W4	4" internal water dam (4" high x 4" diameter) (A2-C3-W and W-31)
-W6	6" internal water dam (4" high x 6" diameter) (A2-C3-W6 and W6-31)
X	Inside caulk outlet, (2", 3", 4", 5" or 6")
-Z	Extended wide flange on body (20" Dia. x 1/4 thick)

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: _____	Page No: _____
Section No: _____	Contractor: _____
Schedule No: _____	Purchase Order No: _____