

Location: \_\_\_\_\_



**R1300T**

**SCUPPER DRAIN WITH ANGLE GRATE  
AND 90 DEGREE THREADED OUTLET**

**Specification:** MIFAB® Series R1300T lacquered cast iron scupper drain with 90 degree threaded outlet, membrane clamp and sloped grate (specify cast iron (Suffix -50) or nickel bronze (Suffix -1)).

**Function:** To provide drainage from a roof surface horizontally where the roof and parapet meet. The angled grate prevents debris from blocking the drainage openings. Reverse outlet for 45 degree outlet connection (R1310).

MODEL NUMBER	A	B	C
R1302,3,4T	7 1/2 [191]	6 3/8 [162]	2 3/4 [70]
R1306,8T	12 1/2 [318]	8 3/8 [213]	3 1/2 [89]

Dimension) Denotes Millimetres

R1300 Series Meets ASME roof drain standard A112.6.4-2003

SUFFIX	OPTIONAL VARIATIONS
-1	Nickel bronze frame and grate
-6	Vandal proof grate
-11	Acid resistant epoxy coating
-13	All Galvanized
-28	Fabricated, Type 304, Stainless Steel Body,Grate and Clamp
-50	Cast iron frame and grate
-83	Stainless steel mesh screen over dome
-BA	Minimum 51% material cost made in the USA
-NH	No Hub Outlet (2", 3", 4," 6" or 8")
-PA	Pennsylvania Steel Act compliant product No

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: \_\_\_\_\_ Page No: \_\_\_\_\_  
 Section No: \_\_\_\_\_ Contractor: \_\_\_\_\_  
 Schedule No: \_\_\_\_\_ Purchase Order No: \_\_\_\_\_