

**MIFAB® , Inc.**  
 1321 West 119th Street  
 Chicago, IL 60643-5109  
 Toll Free (800) 465-2736  
 Phone (773) 341-3030  
 Fax (773) 341-3049  
 Email mail@mifab.com  
 Website www.mifab.com

## MIFAB® - Roof Drains

| Features   | Benefits  |
|--|---|
| A1 modular body with trap seal primer connection Floor drains, area drains, roof drains, cleanouts | Will reduce leftover bodies from jobs.<br>Will eliminate restocking charges and shipping.   |
| Tapped and greased holes.  | Saves time and money.<br>Easier to thread extension rods into tapped and greased holes versus competition's models without this feature.  |
| 3 screws for installation hardware.  | Time and labour savings compared to 4 screws.<br>Time savings – 25%.  |
| All threaded hardware  | Complete range of adjustments to membrane thickness versus standard capped hardware from competition with limited adjustment.   |
| Smaller hole cut in roof A1 body   | MIFAB® – 6-3/8 inches; competition – 8 inches.<br>Additional play with the base from lip of body.   |
| Smaller hole cut in roof A2 body   | MIFAB® – 10 inches; competition – 14 inches.<br>Smaller hole means less chance of a leak.   |
| A2 deep sump body  | MIFAB's 220 cubic inch capacity versus competition's 178 cubic inch capacity.<br>Will drain more effectively because narrower and deeper sump reduces lateral distance of water before draining and provides greater head pressure.<br>Reduced sized cutout in roof deck maintains structural integrity versus larger sized hole in deck.                 |
| A2 body, 3 inch wide membrane clamp  | Has 3 different functions: <ul style="list-style-type: none"> <li>• dome receiver/gravel stop</li> <li>• adjustable extension</li> <li>• underdeck clamp</li> </ul> Eliminates extra parts from others.<br>The wider clamp will more effectively grip the membrane with the tongue and groove design to prevent membrane from pulling out/avoiding leaks. |
| IRMA ballast guard has larger holes  | MIFAB® – 1/2 inch holes; competition – 3/8 inch holes.<br>Less chance of ponding.   |
| Only adjustable IRMA roof drain  | On the roof you can vary the height due to the thickness of the insulation versus standard fix by competition.  |
| Dome has 30% more free area  | MIFAB® - 136 sq. inches; competition – 102 sq. inches.<br>Less chance of ponding.<br>Less possibility of collapse.  |
| PVC/ABS bodies   | For lighter and quicker installation.<br>No MJ clamp required.  |
| No gaskets with MIFAB's adjustable extension   | Gaskets can be lost and/or damaged and are subject to expansion and contraction in various weather conditions, resulting in leaks.  |
| Extensions   | Time saving installation.<br><b>Save money.</b><br>Fewer parts.<br>No gaskets required.<br>Adjustable all threaded rods.<br>No sump receiver because body is elevated off the deck, resulting in cost savings.  |