

Location: _____



T100-PGE-4-ADA-13

**Galvanized Ductile Iron Longitudinal Slotted
Grate to suit 4" clear opening channels**

Specification: T100-PGE-4-ADA-13 galvanized ductile iron longitudinal slotted grates are independently certified to meet Load Class E tested in accordance with EN 1433 134,800 lbs. 600kN. The grate length is 19.69" (.50 m). The grates utilize the patented "Clipfix" grate locking mechanism. The system (channel and grate) provides longitudinal shift protection.

Grate Free Area
T100-PGE-4-ADA
18.07 Sq. in./ft.

CLIPFIX ADVANTAGE
The MEA polymer concrete and GRP channels are designed for our universal CLIPFIX grate locking mechanism. The system (channel and grate) provides longitudinal shift protection.

GRATE MODEL NUMBER	LENGTH
T100-PGE-4-ADA-13	19.69" (500 mm)

LOAD CLASS E		Compliance	
BUILDING SUCCES	EN 1433 134,800 LBS., 600kN, 2,785 PSI	ADA	HEELPROOF

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: _____	Page No: _____
Section No: _____	Contractor: _____
Schedule No: _____	Purchase Order No: _____