


Location: _____




T300-PGE-4-ADA

Ductile Iron Longitudinal Slotted Grate to suit
12" clear opening channels

Specification: T300-PGE-4-ADA ductile iron longitudinal slotted grates are independently certified to meet Load Class E tested in accordance with EN 1433 134,800 lbs. 600kN. The grate length is 19.69" (.50 m). The grates utilize the patented "Clipfix" grate locking mechanism. The system (channel and grate) provides longitudinal shift protection..







Grate Free Area
T300-PGE-4-ADA
19.07 Sq. in./ft.



CLIPFIX ADVANTAGE

The MEA polymer concrete and GRP channels are designed for our universal CLIPFIX grate locking mechanism. The system (channel and grate) provides longitudinal shift protection.

GRATE MODEL NUMBER	LENGTH
T300-PGE-4-ADA	19.69" (500 mm)

LOAD CLASS E		Compliance	
			
EN 1433 - 134,800 LBS., 600kN, 2,785 PSI		ADA	HEELPROOF

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: _____

Page No: _____

Section No: _____

Contractor: _____

Schedule No: _____

Purchase Order No: _____