

Location: _____




TOS

TOP SET® DOUBLE ADJUSTABLE FINISHED FLOOR CLEANOUT TOP ASSEMBLY

Specification: MIFAB® Series TOS-(* (* specify top assembly material) Top Set® finished floor cleanout top assembly with securing and adjustable hardware, and scoriated combined gasketed heavy duty stainless steel cover with stainless steel allen key screws. Cover can be adjusted vertically and side to side after the pour with 1/2" thick composite protective cover and indicating whisker.

Function: Used in finished floors to provide emergency access to the plumbing lines for removal of blockages. Replacement of the surface level cover/plug with the neoprene gasket glued to the underside provides visual evidence that the cleanout has been properly resealed to prevent harmful sewer gases from entering the building. The patented MIFAB® Top Set® finished floor cleanout ships complete with a 1/2" thick plastic cover to protect the cleanout during the concrete pour. The installer pours the concrete to the top level of the plastic cap. Channel locks are used to remove the cover after the concrete pour has settled. Then, remove the solid cleanout cover and use a Phillip's head screwdriver to engage the three screws located underneath the cover. Turn the screws the same amount to elevate the cover up to the finished floor. Turn the screws a different amount to tilt the cover to the same angle as the finished floor.



TOP ASSEMBLY DIAMETER	TOP ASSEMBLY ADJUSTMENT		ANSI / ASME RATING LOAD RATING Lbs.	
	MIN	MAX	N.B. (-1)	S.S. (-3)
5" (127)	1/2" (13)	2 1/2" (64)	Up to 2,000	5,000 to 7,499

SUFFIX	OPTIONAL VARIATIONS
-1	Nickel Bronze
-3	Stainless Steel (Type 304)
-6	Security Screws (TR25 Torx and pin - H-1039A)
-49	Polished Chrome

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: _____ Page No: _____
 Section No: _____ Contractor: _____
 Schedule No: _____ Purchase Order No: _____