

Location: _____



TS

TOP SET HEELPROOF STRAINER

Specification: MIFAB® Series TS(*)-(**) (*specify strainer diameter, ** specify strainer material) MIFAB Top Set heelproof strainer that can be adjusted vertically and side to side after the pour with a 1/2" thick composite strainer protective cover and indicating whisker. Complete with securing and adjustable hardware and allen key vandal resistant stainless steel grate screws.

Function: Used in showers, kitchens, restrooms, and other non-membrane finished areas. Round adjustable heelproof strainer is used for all types of poured finished floors. The concrete is poured to the same level as the orange cap. After the pour, the cap is removed with channel locks and the three Phillips head screws underneath the grate can be engaged to raise the strainer vertically and to also adjust it side to side

VANDAL PROOF ALLEN KEY STAINLESS STEEL SCREWS

PROTECTIVE CAP WITH WHISKER

TOP SET HEELPROOF STRAINER

SCREWS THAT PROVIDE VERTICAL SIDE TO SIDE ADJUSTMENT AFTER THE CONCRETE POUR

TS5-1	5" Round Nickel Bronze Top Set Strainer
TS5-3	5" Round Stainless Steel Top Set Strainer
TS6-1	6" Round Nickel Bronze Top Set Strainer
TS6-3	6" Round Stainless Steel Top Set Strainer

STRAINER DIAMETER	FREE AREA	ANSI / ASME RATING LOAD RATING Lbs.		WT. Lbs.	STRAINER ADJUSTMENT	
		N.B. (-1)	S.S. (-3)		MIN	MAX
5" (127)	8 in ² (5200 ²)	Up to 2,000	5,000 to 7,499	1.25	1/2" (13)	2 1/2" (64)
6" (152)	9 in ² (5800 ²)	Up to 2,000	5,000 to 7,499	1.75	11/16" (17)	2 1/2" (64)

SUFFIX	OPTIONAL VARIATIONS
-1	Nickel Bronze
-3	Stainless Steel (Type 304)
-6	Security Screws (TR25 Torx and pin - H-1039A)
-49	Polished Chrome

CALIFORNIA PROPOSITION 65 WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: _____ Page No: _____
 Section No: _____ Contractor: _____
 Schedule No: _____ Purchase Order No: _____