

C1200-C-US

ISOLATION FLOOR CLEANOUT MODEL VARIATIONS

C1200-C-US FLOOR CLEANOUT WITH SQUARE TOP AND TERRAZZO RECESS

MODEL NUMBER	WT.Lbs	COVER SIZE	OUTLET SIZE	LACQUERED CAST IRON BODY WITH NICKEL BRONZE (-1) OR STAINLESS STEEL (-3)
C1202-C-US	19.25	5" x 5"	2"	\$2,686.00
C1203-C-US	18.75	5" x 5"	3"	\$2,686.00
C1204-C-US	19.25	5" x 5"	4"	\$2,686.00
C1205,6-C-US	19.75	5" x 5"	5", 6"	\$3,404.00

C1200-C OPTIONAL VARIATIONS

SUFFIX	DESCRIPTION	LIST PRICE
-4	Ductile iron top assembly	See above
-6	Security screws (TR25 Torx and pin) (H-1039A)	\$96.00
-11	All acid resistant epoxy coated	\$1,325.00
-13	All galvanized	\$1,325.00
-28	All 304 Stainless steel bodies (2",3",4" No Hub Only)	\$3,162.00
-30	PVC socket connection body* (2",3",4")	No Add
-31	ABS socket connection body* (2",3",4")	No Add
-34	T-cone plug and gasket (C1440 Series)	\$477.00
-95	Client logo (-3 only)	\$1,175.00
NH	No hub outlet (2", 3", 4")	Standard
P	Push on outlet (2", 3", 4")*	No Add
T	Threaded outlet (2", 3", 4")	\$107.00
X	Inside caulk outlet (2", 3", 4")	No Add

Specify POG-6 for C.I. pipe and POG-6-PVC for 6" PVC pipe. 2", 3", 4" sizes use same gasket.