

C1200-C-XR

ISOLATION FLOOR CLEANOUT MODEL VARIATIONS

C1200-C-XR FLOOR CLEANOUT WITH HEAVY DUTY ROUND TOP

MODEL NUMBER	WT.Lbs	COVER SIZE	OUTLET SIZE	LACQUERED CAST IRON BODY WITH:	
				DUCTILE IRON (-4)	NB (-1) OR SS (-3)
C1202-C-XR	16.75	5" Round	2"	\$1,851.00	\$2,435.00
C1203-C-XR	16.25	5" Round	3"	\$1,851.00	\$2,435.00
C1204-C-XR	16.75	5" Round	4"	\$1,851.00	\$2,435.00
C1205,6-C-XR	16.75	5" Round	5", 6"	\$2,569.00	\$3,153.00

C1200-C OPTIONAL VARIATIONS

SUFFIX	DESCRIPTION	LIST PRICE
-4	Ductile iron top assembly	See above
-6	Security screws (TR25 Torx and pin) (H-1039A)	\$96.00
-11	All acid resistant epoxy coated	\$1,325.00
-13	All galvanized	\$1,325.00
-28	All 304 Stainless steel bodies (2", 3", 4" No Hub Only)	\$3,162.00
-30	PVC socket connection body* (2", 3", 4")	No Add
-31	ABS socket connection body* (2", 3", 4")	No Add
-34	T-cone plug and gasket (C1440 Series)	\$477.00
-95	Client logo (-3 only)	\$1,175.00
NH	No hub outlet (2", 3", 4")	Standard
P	Push on outlet (2", 3", 4")*	No Add
T	Threaded outlet (2", 3", 4")	\$107.00
X	Inside caulk outlet (2", 3", 4")	No Add

Specify POG-6 for C.I. pipe and POG-6-PVC for 6" PVC pipe. 2", 3", 4" sizes use same gasket.