

R1100

STANDARD ROOF DRAIN

LACQUERED CAST IRON BODY WITH

MODEL NUMBER	WT.Lbs	OUTLE SIZE	POLY DOME (STANDARD)	LIST-PRICE
R1102, 3, 4	7.00	2", 3", 4"	\$880.00	\$1,035.00

R1100, R1100-EU, R1100-F, and R1100-G VARIATIONS

SUFFIX	DESCRIPTION	LIST PRICE
-6	Vandal proof (Metal dome only)(H-1029)	\$197.00
-11	Acid resistant epoxy coated body, membrane clamp & dome	\$1,264.00
-12	Galvanized metal dome (add to -M price)	\$241.00
-12A	Galvanized body and membrane clamp	\$334.00
-13	Galvanized body, membrane clamp and dome (add to -M price)	\$570.00
-28	Stainless steel body (Type 304) (2", 3", 4" No Hub only)	\$2,005.00
-30	PVC socket connection body*(2", 3", 4")	No Add
-31	ABS socket connection body*(2", 3", 4")	No Add
-81	Rough bronze dome add (A1-MD-81)	\$583.00
-83	Stainless steel mesh screen over metal dome (A1-SSD)	\$583.00
-90	Threaded side outlet (2", 3", 4") (N/A -30, -31) No Add for -NH	\$366.00
-B	Sump Receiver add (A1-BP)	\$429.00
-E	Adjustable extension	\$572.00
-EG	Galvanized adjustable extension	\$1,084.00
-F1.-F2.-F3	Accuflow (parabolic weir) (adj. to 1, 2 or 3 slots)	\$718.00
-G	Ballast guard (A1-BG)	\$767.00
-JC	Ballast guard with secondary clamp	\$1,018.00
-M	Metal dome (A1-MD) (to poly dome)	\$155.00
P	Push on outlet	No add
-R	2" External water dam (A1-WD)	\$326.00
T	Threaded outlet (2", 3", 4")	\$138.00
-U	Underdeck clamp (A1-C3) (2", 3", 4" and 5" NH)	\$251.00
-W	Adjustable water dam (W-31)	\$326.00
-W-1	Waterproofing flange (A1-W-1)	\$488.00
-Z	Extended wide flange on body (13" Dia. x 1/8" thick)	\$2,187.00
X	Inside caulk outlet (2", 3", 4")	No add
5	5" No hub outlet	\$897.00
5T	5" Threaded outlet	\$897.00
5X	5" Inside caulk outlet	\$897.00
6	6" No hub outlet (Not available with -U)	\$897.00
6P	6" Push on outlet* (Not available with -U)	\$897.00

* Add NH to -90 for no hub side outlet - No Add

* PVC/ABS Socket bodies available for 2", 3", 4" connection sizes

NOTE: Underdeck clamp for A1-4X-7, A1-4P-7 and all 5" No hub outlet A1 bodies. (Part # A1-C3-4PO).

Underdeck clamp not available with all 5" threaded and Inside caulk and all 6" outlet bodies.