**MIFAB**<sup>®</sup>

R1200-ES		LARGE SUMP ROOF DRAIN WITH EXTENSION FOR 2" – 9" INSULATION WHEN BODY IS POURED INTO THE DECK			
		LACOUERED CAS	T IRON BODY WITH		
MODEL NUMBER	WT.Lbs	OUTLE SIZE	POLY DOME (STANDARD)	CAST IRON DOME (-M)	
R1200-ES.2. 3. 4	26.5	2", 3",4"	\$2,768.00	\$3,112.00	
R1200-ES.5. 6	27.75	5", 6"	\$3,272.00	\$3,616.00	
R1200-ES.8	31	8"	\$3,775.00	\$4,119.00	
		R1200-ES OPTI	ONAL VARIATIONS		
SUFFIX	DESCRIPTION			LIST PRICE	
6		Vandal proof (Metal dome only)(H-1029)			
11		Acid resistant epoxy coated body, membrane clamp & dome			
12	Galvanized metal do	\$2,238.00 \$605.00			
-12A		Galvanized body and membrane clamp			
-12B		Galvanized metal dome and membrane clamp			
-14		Flat grate			
-28		Stainless steel body (Type 304) (2", 3", 4" NH only)			
-30		PVC socket connection body* (2", 3", 4")			
-31	ABS socket connecti	ABS socket connection body* (2", 3", 4")			
-81		Rough bronze dome (A2-MDL-81)			
-83		Stainless steel mesh screen over metal dome (A2-SSD)			
.90		Threaded side outlet (cast iron only) (2",3",4") (N/A in -30,-31)			
·90		6" threaded side outlet (cast iron only)			
90-NH		No hub side outlet (cast iron only) (2",3",4")(N/A in -30,-31)			
·B		Sump receiver (A2-BP)			
-EG		Galvanized adjustable extension			
·EG		Accuflow (parabolic weir) (adj. to 1, 2 or 3 slots)			
·G		Ballast guard (A2-BG)			
M-80		Low aluminum dome (4 1/4" high) (A2-MDL-80) (to poly dome)			
VI-00 D		Push on outlet, (2",3",4",6") Specify POG-6 for C.I. pipe and POG-6-PVC for PVC pipe, 2", 3", 4" us			
·R		2" external water dam (A2-WD)			
·κ Γ		Threaded outlet, (2", 3", 4", 5" or 6")			
Ū		Underdeck clamp (A2-C3) (A368-DC for 8")			
.U3		Underdeck clamp with cut away side (A2-C3-C0)			
W		Adjustable internal water dam (5" high x 4" diameter) (A2-C3-W and W-31)			
W-1		Water proofing flange (A2-W-1)			
W2		2" internal water dam (2" high x 4" diameter) (A2-C3-W and W-31)			
W2 W3		3" internal water dam (2" high x 4" diameter) (A2-C3-W and W-31)			
W4	5 internal water da	4" internal water dam (3" high x 4" diameter) (A2-C3-W and W-31)			
·W4 ·W6		6" internal water dam (4" high x 4" diameter) (A2-C3-W and W-31)			
			5-VVO allu VVO-31)	\$942.00	
X -Z	Inside caulk outlet, (			No add	
		e on body (20"Dia. x 1/4 thick) connection sizes with transition		\$2,368.00	

\*PVC/ABS Socket bodies available for 2", 3", 4" connection sizes with transition body only. Note: Deck opening - 10" (254) with sump receiver - 15 3/4" (400)