

R1220-EU

MEDIUM SUMP EXTENSION ROOF DRAIN F OR 1 3/4" TO 7" INSULATION

LACQUERED CAST IRON BODY WITH

MODEL NUMBER	WT.Lbs	OUTLE SIZE (NO HUB STANDARD)	CAST IRON DOME (-M)
R1222, 3, 4, 6-EU	26.50	2", 3", 4", 6"	\$2,121.00

R1220, R1220-EU, R1220-G, R1220-JC, R1220-PR, R1220-R AND R1220-RS OPTIONAL VARIATIONS

SUFFIX	DESCRIPTION	LIST PRICE
-6	Vandal proof (Metal dome only) (H-1029)	\$197.00
-11	Acid resistant epoxy coated body, membrane clamp & dome	\$1,679.00
-12	Galvanized metal dome (add to -M Price)	\$213.00
-12A	Galvanized body and membrane clamp	\$550.00
-13	Galvanized body, membrane clamp and dome	\$652.00
-83	Stainless steel mesh screen over dome	\$772.00
-B	Sump receiver (A2-BP-90)	\$452.00
-E	Adjustable extension (See page 110, point #7)	\$835.00
-EG	Galvanized adjustable extension	\$1,874.00
-G	Ballast guard (A5-BG)	\$1,035.00
-HC	Adjustable ballast guard with secondary clamp	\$1,286.00
-JC	Ballast guard with secondary clamp	\$1,286.00
-R	2" external water dam (A5-WD)	\$326.00
-U	Underdeck clamp (A5-C3)	\$251.00
-U3	Underdeck clamp with cut away side (A5-C3-U)	\$251.00
-W-1	Water proofing flange (A5-W-1)	\$733.00
X	Inside caulk outlet (2", 3", 4", 6")	No add
-Z	Extended wide flange on body (20" dia. x 1/4" thick)	\$2,368.00
-5	Cast iron sediment bucket (A2-MB) for R1220-PR only	\$428.00