

R1230

MEDIUM SUMP ROOF DRAIN

LACQUERED CAST IRON BODY WITH

MODEL NUMBER	WT.Lbs	OUTLET SIZE (NO HUB STANDARD)	CAST IRON DOME (-M)
R1232, 3, 4, 6	26.50	2", 3", 4", 6"	\$3,215.00

R1220, R1220-EU, R1220-G, R1220-JC, R1220-PR, R1220-R AND R1220-RS OPTIONAL VARIATIONS

SUFFIX	DESCRIPTION	LIST PRICE
-6	Vandal proof (Metal dome only) (H-1029)	\$197.00
-11	Acid resistant epoxy coated body, membrane clamp & dome	\$1,264.00
-12	Galvanized metal dome (add to -M Price)	\$241.00
-12A	Galvanized body and membrane clamp	\$334.00
-13	Galvanized body, membrane clamp and dome	\$570.00
-83	Stainless steel mesh screen over dome	\$583.00
-B	Sump receiver (A2-BP-90)	\$429.00
-E	Adjustable extension (See page 110, point #7)	\$1,197.00
-EG	Galvanized adjustable extension	\$1,772.00
-G	Ballast guard (A5-BG)	\$1,297.00
-M	Cast iron dome strainer	\$1,361.00
-PA	Pennsylvania Steel Act compliant	\$1,286.00
-BA	Minimum 51% material cost made in the USA	\$326.00
-U	Underdeck clamp (A5-C3)	\$406.00
-U3	Underdeck clamp with cut away side (A5-C3-U)	\$810.00
-W-1	Water proofing flange (A5-W-1)	\$733.00
X	Inside caulk outlet (2", 3", 4", 6")	No add
(Standard)	No hub outlet	\$2,368.00