

Location: _____



P5000

STAINLESS STEEL KETTLE DRAIN

Specification: MIFAB® Series P5000, kettle drain manufactured out of 16 gauge, Type 304 stainless steel with anchor tabs and slotted Load Class "A" Light duty stainless steel loose set full grate with bead blasted finish. Bottom outlets are centered and available in 4", 6" or 8" no hub outlet connections and fabricated as part of the drain. Also available with an optional anchor flange (Suffix -FL) and B, or C load rated grates.

Function: Used in kitchen, restaurant and food processing areas for placement under or within close proximity to the kettles that they will serve. A variety of grate designs are available for the various applications or locations in the cooking area. Type 304 stainless steel construction provides for ease of cleaning, maintenance and sanitary installation. All grate openings are polished to a smooth finish.

ANSI A112.21.1M
Point Drain Light Duty
Load Rated
- up to 2,000 Lbs.

Specifying engineer is responsible for concrete encasement and reinforcing based upon application and local codes.

The P5000-LCB is NSF certified with a load classification of Medium Duty.

OPTIONAL VARIATIONS

MODEL NUMBER	SIZE	MODEL NUMBER	SIZE
P5001	12" x 24"	P5009-96	18" x 96"
P5002	12" x 30"	P5009-108	18" x 108"
P5003	12" x 36"	P5009-120	18" x 120"
P5004	12" x 48"	P5010	24" x 24"
P5004-60	12" x 60"	P5011	24" x 30"
P5004-72	12" x 72"	P5012	24" x 36"
P5004-84	12" x 84"	P5013	24" x 48"
P5004-96	12" x 96"	P5013-60	24" x 60"
P5004-108	12" x 108"	P5013-72	24" x 72"
P5004-120	12" x 120"	P5013-84	24" x 84"
P5005	18" x 18"	P5013-96	24" x 96"
P5006	18" x 24"	P5013-108	24" x 108"
P5007	18" x 30"	P5013-120	24" x 120"
P5008	18" x 36"	P5014	30" x 30"
P5009	18" x 48"	P5015	30" x 36"
P5009-60	18" x 60"	P5016	30" x 48"
P5009-72	18" x 72"	P5017	36" x 36"
P5009-84	18" x 84"	P5018	36" x 48"

- C Membrane Clamp (Includes anchor flange)
- F4 4" Round Stainless Steel Funnel
- FL Anchor Flange
- FSSC 304 Stainless Steel Slotted Grate, Load Class C
- FSPC 304 Stainless Steel Perforated Grate, Load Class C
- NS Anti-Slip grate
- SB Sediment Bucket
- 6 Vandal proof grates (center lock-down)
- 7 1/2" Trap seal primer connection
- 7MG MI-GARD trap seal primer connection
- 20 Bottom outlet strainer (P5000-ST)
- 22 Less Grate
- 29 Type 316 Stainless Steel
- 90 Side Outlet (Specify -2NH, -3NH, -4NH, -6NH)
- 150 Half Grate
- 175 Three Quarter Grate

Note: Every order of this product is a special / custom order fabrication. This product is non-returnable and non-cancellable.

NOTE: Type 316 S.S. product available. Contact MIFAB® for pricing.

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: _____ Page No: _____
 Section No: _____ Contractor: _____
 Schedule No: _____ Purchase Order No: _____